



# DriveLock

## Release Notes 2022.1 SP1

---

DriveLock SE 2022



---

# Table of Contents

|                                                            |           |
|------------------------------------------------------------|-----------|
| <b>1 RELEASE NOTES 2022.1 SP1 (BUILD 22.1.4)</b>           | <b>5</b>  |
| 1.1 Document Conventions                                   | 5         |
| 1.2 Available DriveLock Documentation                      | 5         |
| <b>2 SYSTEM REQUIREMENTS</b>                               | <b>8</b>  |
| 2.1 DriveLock Agent                                        | 8         |
| 2.2 DriveLock Management Console                           | 13        |
| 2.3 DriveLock Enterprise Service                           | 13        |
| 2.4 DriveLock Operations Center (DOC)                      | 15        |
| 2.5 DriveLock in workgroup environments (without AD)       | 15        |
| <b>3 UPDATING DRIVELOCK</b>                                | <b>17</b> |
| 3.1 Migration of databases version 2020.1 and older        | 17        |
| 3.1.1 Requirements for successful migration                | 18        |
| 3.1.2 How to migrate                                       | 18        |
| 3.2 Updating the DriveLock Agent                           | 20        |
| 3.3 Updating the DriveLock Enterprise Service (DES)        | 21        |
| 3.4 General information on updating to the current version | 21        |
| 3.5 Manual Updates                                         | 22        |
| <b>4 VERSION HISTORY</b>                                   | <b>23</b> |
| 4.1 Version 2022.1                                         | 23        |
| 4.1.1 Service Pack 1 2022.1                                | 23        |
| 4.1.2 Bug fixes 2022.1 HF1                                 | 23        |
| 4.1.3 Bug fixes 2022.1                                     | 25        |
| 4.2 Version 2021.2                                         | 33        |
| 4.2.1 Bug fixes 2021.2                                     | 33        |
| 4.3 Version 2021.1                                         | 39        |
| 4.3.1 Bug fixes 2021.1 HF1                                 | 39        |

---

|                                                                |           |
|----------------------------------------------------------------|-----------|
| 4.3.2 Bug fixes 2021.1 .....                                   | 39        |
| 4.4 Version 2020.2 .....                                       | 45        |
| 4.4.1 Bug fixes 2020.2 .....                                   | 45        |
| 4.5 Version 2020.1 .....                                       | 53        |
| 4.5.1 Bug fixes 2020.1 .....                                   | 53        |
| 4.5.2 Bug fixes 2020.1 HF1 .....                               | 61        |
| 4.5.3 Bug fixes 2020.1 HF2 .....                               | 64        |
| 4.5.4 Bug fixes 2020.1 HF3 .....                               | 65        |
| 4.6 Version 2019.2 .....                                       | 69        |
| 4.6.1 Bug fixes 2019.2 .....                                   | 69        |
| 4.6.2 Bug fixes 2019.2 HF1 .....                               | 75        |
| 4.6.3 Bug fixes 2019.2 SP1 .....                               | 77        |
| 4.6.4 Bug fixes 2019.2 HF3 .....                               | 81        |
| <b>5 KNOWN ISSUES .....</b>                                    | <b>83</b> |
| 5.1 DriveLock Management Console .....                         | 83        |
| 5.2 Known limitations on the agent .....                       | 83        |
| 5.3 DriveLock Enterprise Service (DES) .....                   | 83        |
| 5.4 Installing Management Components with Group Policies ..... | 83        |
| 5.5 Self Service Unlock .....                                  | 83        |
| 5.6 DriveLock, iOS and iTunes .....                            | 83        |
| 5.7 DriveLock Device Control .....                             | 84        |
| 5.8 DriveLock Disk Protection .....                            | 85        |
| 5.9 DriveLock File Protection .....                            | 88        |
| 5.10 DriveLock Pre-Boot Authentication .....                   | 89        |
| 5.11 Encryption .....                                          | 90        |
| 5.12 DriveLock Mobile Encryption .....                         | 90        |
| 5.13 BitLocker Management .....                                | 91        |

|                                              |           |
|----------------------------------------------|-----------|
| 5.14 DriveLock Operations Center (DOC) ..... | 92        |
| 5.15 DriveLock Security Awareness .....      | 93        |
| 5.16 DriveLock and Thin Clients .....        | 93        |
| <b>6 END OF LIFE ANNOUNCEMENT .....</b>      | <b>94</b> |
| <b>7 DRIVELOCK TEST INSTALLATION .....</b>   | <b>96</b> |
| <b>COPYRIGHT .....</b>                       | <b>97</b> |

# 1 Release Notes 2022.1 SP1 (Build 22.1.4)

These release notes contain [important information](#) about new features and improvements, bug fixes and known issues in the current version of DriveLock. Also included in the release notes are changes or additions not yet covered in the documentation.

You can find the complete DriveLock documentation at [DriveLock Online Help](#).

## 1.1 Document Conventions

Throughout this document the following conventions and symbols are used to emphasize important points that you should read carefully, or menus, items or buttons that you need to click or select.

 Warning: Red text points towards risks which may lead to data loss.

 Note: Notes and tips contain important additional information.

**Menu items** or names of **buttons use bold formatting**. *Italics* represent fields, menu commands, and cross-references.

`System font` represents messages or commands typed at a command prompt.

A plus sign between two keyboard keys means that you must press those keys at the same time. For example, ALT+R means that you must hold down the ALT key while you press R. A comma between two or more keys means that you must press them consecutively. For example 'ALT, R, U' means that you must first press the Alt key, then the R key, and finally the U key.

## 1.2 Available DriveLock Documentation

 Note: We will update our documentation more frequently and independently of DriveLock releases in the future as a result of ongoing restructuring and maintenance. Please find our latest versions at [DriveLock Online Help](#).

The DriveLock documentation consists of the following documents as of now:

### DriveLock Installation

Here you get information how to install the different DriveLock components.

 Note: Note that customers of DriveLock Managed Security Services are provided with alternative installation information.

## DriveLock Administration

 Note: We are currently revising the documentation related to the DriveLock administration. For this reason, we will temporarily provide two versions with different content. In addition, some content is currently only available and up to date in German, the English version will be added as soon as possible.

- The new **DriveLock Administration** documentation provides a brief introduction to the DriveLock Operations Center (DOC), and information on using the DriveLock Management Console (DMC) and the DriveLock Policy Editor.
- In this version, the old **Administration Guide** still contains chapters on the following topics: Device Control, Network Profiles, File Protection and information about using DriveLock with Terminal Servers.

## DriveLock User Guide

The DriveLock User Guide contains the documentation of all features available to the end user (temporary unlock, encryption and private network profiles). The user guide is intended to help end users find their way around the options available to them.

## DriveLock Application Control

This documentation contains all the information you need to employ DriveLock Application Control.

## DriveLock Encryption

The following features are included in this documentation:

- **DriveLock BitLocker Management**  
This chapter details the required configuration settings and functionality DriveLock provides for hard disk encryption with Microsoft BitLocker.
- **DriveLock Disk Protection**  
This chapter explains the configuration settings required for DriveLock Disk Protection (formerly known as FDE).
- **DriveLock Pre-Boot Authentication**  
This chapter explains the procedure for setting up and using DriveLock PBA to authenticate users, and provides solutions for recovery or emergency logon.

- **DriveLock Network Pre-Boot Authentication**

This chapter describes the configuration for pre-boot authentication for use within a network.

- **DriveLock BitLocker To Go**

In this chapter you will find all the necessary configuration settings to integrate BitLocker To Go into DriveLock.

- **DriveLock Encryption 2-Go**

This chapter provides information on how Encryption 2-Go handles the encryption of external data media (such as USB flash drives or SD cards).

### **DriveLock DOC Companion**

This is a quick introduction to the DOC Companion tool which acts as an interface between the DriveLock Operations Center (DOC) and the DriveLock Management Console (DMC).

### **Microsoft Defender Management**

This document describes how to integrate and configure Microsoft Defender in DriveLock.

### **DriveLock Events**

This document contains a list of all current DriveLock events with descriptions.

### **DriveLock Linux Agent**

This document explains how to install and configure the DriveLock Agent on Linux clients.

### **DriveLock Security Awareness**

This document covers the security awareness features that are the foundation of the DriveLock Security Awareness Content product.

### **Vulnerability Scanner**

This document covers the vulnerability scanning functionality, its configuration settings and usage in DriveLock Operations Center (DOC) and DriveLock Management Console.

## 2 System Requirements

This section contains recommendations and minimum requirements. The requirements may vary depending on your configuration of DriveLock, its components and features, and your system environment.

### 2.1 DriveLock Agent

Before distributing or installing the DriveLock agents on your corporate network, please ensure that the computers meet the following requirements and are configured properly to provide full functionality.

#### Main memory:

- at least 4 GB RAM

#### Free disk space:

- approx. 1 GB with average policies that do not include your own video files
- at least 2 GB if Security Awareness campaigns are used with video sequences (Security Awareness Content AddOn)



Note: How much disk space you need largely depends on how DriveLock agents are configured via policies and on the settings and features they contain. It is therefore difficult to provide an exact specification here. We recommend that you verify and determine the exact value in a test setup with a limited number of systems before performing a company-wide roll-out.

#### Additional Windows components:

- .NET Framework 4.6.2 or newer (For security awareness campaigns in general)
- KB3140245 must be installed on Windows 7  
Please find further information [here](#) and [here](#).  
Without this update, WinHTTP cannot change any TLS settings and the error 12175 appears in the dlwsconsumer.log und DLUpdSvx.log log files.
- KB3033929 (SHA-2 code signing support) must be installed on Windows 7 64 bit.

#### Supported platforms:

DriveLock supports the following Windows versions for the listed agent versions:

| OS version            | 2022.1 | 2021.2 | 2021.1 | 2020.2 |
|-----------------------|--------|--------|--------|--------|
| Windows 11 Pro        |        |        |        |        |
| Windows 11 21H2       | +      | +      | -      | -      |
| Windows 10 Pro        |        |        |        |        |
| Windows 10 21H2       | +      | +      | +      | +      |
| Windows 10 21H1       | +      | +      | +      | +      |
| Windows 10 20H2       | +      | +      | +      | +      |
| Windows 10-1909       | -      | -      | +      | +      |
| Windows 11 Enterprise |        |        |        |        |
| Windows 11 21H2       | +      | +      | -      | -      |
| Windows 10 Enterprise |        |        |        |        |
| Windows 10 21H2       | +      | +      | +      | +      |
| Windows 10 20H2       | +      | +      | +      | +      |
| Windows 10-1909       | +      | +      | +      | +      |
| Windows 10-1809       | -      | -      | +      | +      |
| Windows 10-1803       | -      | -      | +      | +      |

| OS version                             | 2022.1 | 2021.2 | 2021.1 | 2020.2 |
|----------------------------------------|--------|--------|--------|--------|
| Windows 10 Enterprise LTSC             |        |        |        |        |
| Windows 10 Enterprise 2021 LTSC (21H2) | +      | +      | -      | +      |
| Windows 10 Enterprise 2019 LTSC (1809) | +      | +      | +      | +      |
| Windows 10 Enterprise 2016 LTSC (1607) | +      | +      | +      | +      |
| Windows 10 Enterprise 2015 LTSC (1507) | +      | +      | +      | +      |
| Windows Server                         |        |        |        |        |
| Windows Server 2022                    | +      | +      | +      | +      |
| Windows Server 2019                    | +      | +      | +      | +      |
| Windows Server 2016                    | +      | +      | +      | +      |
| Windows Server                         | +(*)   | +(*)   | +(*)   | +(*)   |

| OS version                                                                 | 2022.1                   | 2021.2                   | 2021.1                   | 2020.2                   |
|----------------------------------------------------------------------------|--------------------------|--------------------------|--------------------------|--------------------------|
| 2012 R2                                                                    |                          |                          |                          |                          |
| Older Windows versions                                                     |                          |                          |                          |                          |
| Windows 8.1                                                                | +                        | +                        | +                        | +                        |
| Windows 7 SP1                                                              | +                        | +                        | +                        | +                        |
| Windows XP                                                                 | Support license required | Support license required | Support license required | Support license required |
| The following Linux derivatives and newer versions (own DriveLock license) |                          |                          |                          |                          |
| CentOS 8                                                                   | - (**)                   | +                        | +                        | +                        |
| Debian 11                                                                  | +                        | +                        | +                        | +                        |
| Fedora 34                                                                  | +                        | +                        | +                        | +                        |
| IGEL OS 11.05                                                              | +                        | +                        | +                        | +                        |
| Red Hat Enterprise Linux 5                                                 | +                        | +                        | +                        | +                        |
| SUSE 15.3                                                                  | +                        | +                        | +                        | +                        |
| Ubuntu 20.04                                                               | +                        | +                        | +                        | +                        |

Please note the important note in the [Supported Platforms](#) section.

DriveLock version 2022.1 and later will no longer support CentOS Linux 8, as it has reached its End of Life date on 12/31/2021.

 Warning: We recommend that all our customers install our latest version.

The Windows DriveLock Agent is available for AMD/Intel X86 based systems (32-bit and 64-bit architecture). We recommend using a 64 bit system for the DriveLock Agent. Server operating systems are being tested on 64 bit only.

### Notes on Linux

- DriveLock Application Control requires Linux kernel version > 5 for use on Linux agents.
- Application Control cannot be used with IGEL OS.

 Note: For more information about the Linux client and the limitations of its functionality, please refer to the separately available Linux documentation at [DriveLock Online Help](#).

### Restrictions

- Using DriveLock Disk Protection on XP is no longer supported.
- Windows XP Embedded: Do not install the DriveLock Virtual Channel and the DriveLock Agent on the same client!
- BitLocker Management is supported on Windows 7 systems only with TPM and only for 64-bit.
- Disk Protection UEFI and GPT partitioning are supported for drives up to max. 2 TB for Windows 8.1 64 bit or newer and UEFI version V2.3.1 or newer.
- Disk Protection is released for Windows 10 from version 1703 for the previously mentioned Windows versions (see [Known Issues](#)).
- Starting with version 2019.2, the agent status is a separate option and should be explicitly configured. The default setting is not to display a status.

 Note: Microsoft discontinues support for its Windows 7 operating system as of January 2020. However, DriveLock will continue to support Windows 7 with a regular client license. We will notify our customers in time when Windows 7 is eligible for extended legacy support. At the earliest, this will be the case after DriveLock version 2022.2 is released.



Note: If you are running Windows 7, we recommend that you use the most current version. DriveLock does not distinguish between standard Windows license or ESU (Extended Security Update key). (Reference EI-1349)

## Citrix environments

The DriveLock Agent requires the following systems to be able to make full use of the DriveLock Device Control feature:

- XenApp 7.15 or newer (ICA).
- Windows Server 2012 R2 or 2016 (RDP).
- Creating DriveLock File Protection encrypted folders on Terminal Service is not supported.

## 2.2 DriveLock Management Console

Before you install the DriveLock Management Console, please make sure that the computer meets all of these requirements to ensure full functionality.

### Main memory:

- at least 4 GB RAM

### Free disk space:

- approx.350 MB

### Additional Windows components:

- .NET Framework 4.8 or higher

### Supported platforms:

The Management Console 2022.1 SP1 has been tested and approved on the latest versions of Windows that were officially available at the time of release and that have not yet reached the end of the service period provided by Microsoft. Please check the [DriveLock Agent](#) chapter for a list of Windows versions that DriveLock supports.



Warning: Starting with DriveLock version 2021.2, we no longer provide a 32-bit version of the DMC.

## 2.3 DriveLock Enterprise Service

Before distributing or installing the DriveLock Enterprise Service (DES) on your corporate network, please ensure that the computers meet the following requirements and are

configured properly to provide full functionality.

**Main memory / CPU:**

- at least 8 GB RAM, CPU x64 with 2,0GHz and EM64T (Extended Memory Support)

**Free disk space:**

- at least 4 GB, with policies that do include Security Awareness campaigns with video sequences (Security Awareness Content AddOn), approx. 15 GB is recommended
- if the server is also running the SQL-Server database, additional 10 GB are recommended for storing DriveLock data

**Additional Windows components:**

- .NET Framework 4.8 or higher is required for installation!



Note: Depending on the number and duration of the DriveLock events that are stored, the size of the DriveLock database can vary greatly from one system environment to another. It is therefore difficult to provide an exact specification here. We recommend setting up a test environment with the planned settings over a period of at least a few days to determine the exact values. These values can be used to calculate the required memory capacity.

**Required DriveLock API Services Ports (DOC/MQTT):**

- 5370, 6369 and 4369: These three ports should not be occupied by other server services, but they do not have to be accessible from outside (internal only)
- 8883: The agents connect to the DES on this port so that they can be accessed by agent remote control. The DES installation program automatically enables the clearance in the local firewall of the computer.

**Supported platforms:**

- Windows Server 2012 R2 64-bit (minimum requirement for the DriveLock Operations Center)



Note: Please make sure you have installed SQL Express 2017 under Windows Server 2012 R2 before you can successfully install DriveLock version 2020.1.

- Windows Server 2016 64-bit
- Windows Server 2019 64-bit
- Windows Server 2022 64-bit

On Windows 10 client operating systems, use a DES as a test installation only.

 Warning: Starting with DriveLock version 2020.1, we no longer provide a 32-bit version of the DES.

### Supported databases:

- SQL Server 2012 (minimum requirement for the DriveLock Operations Center) or newer
- SQL Server Express 2017 or newer (for installations with up to 200 clients and test installations)

 Warning: The DES requires the **Microsoft SQL Server 2012 Native Client version 11.4.7001.0**. In case this component is not yet installed, this happens automatically before the DES is actually installed. If an older version is already installed, it will be updated automatically.

 Note: Please refer to the applicable Microsoft documentation regarding the system requirements for installing the SQL database or SQL Express.

 Warning: The database connection between the DriveLock Operations Center and the database requires a TCP/IP connection.

## 2.4 DriveLock Operations Center (DOC)

As of version 2021.2, we no longer include an MSI installer for installing the DriveLock Operations Center (DOC.exe) locally. We integrated all of the functions provided in the DOC.exe in other ways into our DOC platform (DOC Companion). That way, there is no need for an additional application.

 Note: The web-based DriveLock Operations Center is included in the DES installation and is not a stand-alone component. It is accessed via a browser.

DriveLock Operations Center is only available for AMD / Intel X86 based 64-bit systems.

Please also note the following [information](#).

## 2.5 DriveLock in workgroup environments (without AD)

DriveLock can also be used without Active Directory. Note the following, amongst other things:

- The rights and roles concept for the administrators / helpdesk staff can only be established from local users
- It is not possible to assign policies and whitelist rules to AD groups, AD users, AD OUs, but only to local objects (computer names and users).
- The name resolution must work, because the DriveLock Operations Center (DOC) accesses the clients via the NETBIOS/FQDN name (important for all Helpdesk activities).
- If DNSSD is disabled, you have to know your clients in detail as there is no AD inventory.
- It is possible to log on to DriveLock Operations Center (DOC) with a local user in work-group environments
- Agent remote control can be used to access clients (incl. Push Install) only if all clients are installed with a default administrative user
- In this context, it is common to have environments without a DES Server (only DriveLock Agent with local configuration) or DES Servers that distribute a configuration file via HTTP web server

## 3 Updating DriveLock

If you are upgrading to **newer** versions of DriveLock, please note the following information.

### 3.1 Migration of databases version 2020.1 and older

When updating from DriveLock 2020.1 (or older) to 2020.2 or newer, the two DriveLock databases are merged. The data from the DriveLock-DATA database will be migrated to the DriveLock database.

As of version 2020.2, the DriveLock-DATA database is no longer used and can be archived or deleted after migration. This applies both to the main "root" databases and to the tenant databases, if used.

If necessary, custom SQL jobs created for maintenance and backup need to be adjusted. This also applies to any queries and tools you may have created that use the DriveLock DATA.

#### Database Migration Wizard

The wizard is automatically started by the database installation wizard after completing a successful update.

 Warning: Make sure to back up all DriveLock databases before database migration.

- The Database Migration Wizard analyzes all DriveLock databases and checks whether data should be migrated and how much data needs to be migrated. Based on the data found, it proposes how to configure the migration.

 Note: It is possible to interrupt and resume the migration process at any time. No data is lost.

- The following data is migrated from the DriveLock-DATA database to the DriveLock database:
  - EDR categories
  - EDR alerts
  - Event data
  - Security Awareness Sessions

 Note: Any EDR categories you have created will need to be migrated to ensure EDR functionality after the update. Events, EDR alerts and Security Awareness Sessions can also be migrated later. We recommend that you migrate only the important data first and schedule the migration of bulk data at a time when activity is low.

### 3.1.1 Requirements for successful migration

Start the Database Migration Wizard as administrator so that it can access the registry area of the DES configuration and start the DES service if necessary.

Note the following for remote SQL servers:

- Database Migration Wizard uses Microsoft Distributed Transaction Coordinator (MSDTC) to ensure data integrity across databases during migration.
- For remote SQL servers, MSDTC configuration may be required.

 Note: An error message will be displayed if this step is necessary.

- MSDTC Configuration: <https://docs.microsoft.com/en-us/troubleshoot/windows-server/application-management/enable-network-dtc-access>
- MSDTC Firewall Configuration: <https://docs.microsoft.com/en-us/troubleshoot/windows-server/application-management/configure-dtc-to-work-through-firewalls>

### 3.1.2 How to migrate

You can accept the default options that are already configured in the Database Migration Wizard; we recommend that you only modify them in certain cases.

This process goes through the following steps:

1. Connect to the main database

The first step is to perform a connection test to the main DriveLock database, reading the connection data from the registry.

 Note: In case you want to change the default settings, click the **Advanced Mode** button (see 3.).

2. Analyze the databases

After testing the connection, the wizard analyzes the data in the databases.

Then, it determines the connection parameters to the event databases and, if available, the tenant databases from the main DriveLock database.

The wizard checks the connection and version to each database. The databases must be up to date to support migration.



Note: If the version of a database is not up to date, please use the Database Migration Wizard to update the database and start the migration again.

### 3. Configure data migration settings

This step is only displayed in **Advanced Mode**. Migration is configured on a per-client basis and provides the following customization options:

- Prepare databases

This option runs the database maintenance (index maintenance) on both databases and automatically prepares the event data to ensure a more efficient migration.

- Migrate event data

This option migrates the events as they can be evaluated in the reports in the DOC.

- Reprocess events after migration

This option is necessary to create the links from the events to the other data such as computers, users, drives, devices, etc. The events are displayed in the DOC in Related Entities.

The processing of this data may take some time for larger amounts of data. When the DriveLock Enterprise Server is running, this will happen in the background.

- Check for existing events

Use this setting to check whether the data in the target database has already existed before the migration. This may be the case if you migrate the data at a later point in time. This option can be turned off to speed up the migration. If errors occur, we recommend repeating the migration and checking the data. In case an error occurs, no data will be lost.

- Migrate security awareness session data
- Migrate EDR categories
- Migrate EDR alerts data
- Processing batch sizes

#### 4. Database migration processing

- The databases are migrated one after the other, depending on the tenant. You can stop the migration and start it again. The output shows the progress of the migration.
- Migrated data is deleted from the source database (here the event database).
- After successful migration, the DriveLock Enterprise Service is started.



Note: When the migration is finished, the event databases are no longer needed and can be archived or deleted.

### 3.2 Updating the DriveLock Agent

**Please note the following when you update the DriveLock Agent to a newer version:**

#### 1. Before starting the update:

- Check whether the DriveLock Update Service **dlupdate** is running on your system; if it is, make sure to remove it.
- If you update the agent with DriveLock's auto update functionality, specify the **Automatic update setting** in the DriveLock policy:
  - Check the **Perform reboot to update the agent** checkbox and set the value for a user-deferred installation to **0**, to keep the time to restart the computer as short as possible.
- Please also specify the following **settings**:
  - **Run DriveLock Agent in unstopable mode**: Disabled
  - **Password to uninstall DriveLock**: Not configured
- If you are working with one of DriveLock's encryption features, make sure to specify a minimum of 5 days as decryption delay in the encryption settings in case of uninstallation.
- If you are using BitLocker Management, make sure to consider the following before you update:

For details, see the BitLocker Management documentation at [DriveLock Online Help](#).

The **Do not decrypt** encryption setting prevents a possible change in the encryption status of the DriveLock Agents. Before updating, make sure to enable this option in the current encryption policy and save and publish the policy afterwards.

2. During the update:
  - Run the update with a privileged administrator account. This is automatically true for the auto update.
3. After the update:
  - You must reboot the client computers after the DriveLock Agent has been updated so that the driver components are updated, too. If you are using a software deployment tool for the update, add this step to the update procedure or restart the updated computers manually.

### 3.3 Updating the DriveLock Enterprise Service (DES)

When updating the DES from version 2021.1 to higher versions, please note the following:

To perform the update successfully, you need a valid license including maintenance. It must be stored in your currently running system in the database of the DES or renewed and uploaded via the DMC before starting the update.

### 3.4 General information on updating to the current version

The DriveLock Installation Guide explains all the steps you need to take to update to the latest version. The Release Notes include some additional information you should be aware of when updating your system.

**Warning:** The existing self-signed DES certificate can no longer be used when updating from version 7.x to 2019.1 or higher and will be replaced by a newly generated certificate. The new certificate can be created automatically as a self-signed certificate and stored in the certificate store of the computer. When updating from 2019.1 or higher to newer versions, however, you can continue to use the self-signed DES certificate.

### Updating the DriveLock Management Console (DMC)

When updating from DriveLock version 7.7.x to higher versions, please use the following workaround to update the DMC: Rename the `DLFdeRecovery.dll` and then reinstall the DMC.

### Disk Protection Update

After updating the DriveLock Agent, any existing Disk Protection (also known as FDE) installation will be automatically updated to the latest version without re-encryption. After updating the FDE, a restart may be required.

For further information on updating DriveLock Disk Protection or updating the operating system where DriveLock Disk Protection is already installed, see our separate document

available for download from our website [www.drivelock.help](http://www.drivelock.help).

### 3.5 Manual Updates

If you do not use GPO to distribute the policies, a manual update of the agent on Windows 8.1 and later fails if DriveLock Agent.msi was launched from Windows Explorer (e.g., by double-clicking) and without permissions of a local administrator. Start the MSI package from an administrative command window via `msiexec` or use `DLSetup.exe`.

#### Update from older to newer DriveLock versions

If you update manually by starting `msiexec` or `DLSetup.exe`, it may happen that Windows Explorer does not close correctly. As a result, the Windows user interface disappears (black screen) and does not restart even after the agent update. If this happens, you will have to start the Explorer manually via the Task Manager or initiate a reboot. This mainly affects customers who are using client management software that may be running the `msiexec` in a user session. The problem can be solved by adding the following parameters to the `msiexec` call:

- `MSIRESTARTMANAGERCONTROL=Disable`
- `MSIRMSHUTDOWN=2`

## 4 Version History

This version history lists the changes / new features compared to the previous DriveLock version.

### 4.1 Version 2022.1

#### 4.1.1 Service Pack 1 2022.1

The 2022.1 Service Pack 1 features new security awareness content packages in a new design, plus an improved look and feel for existing packages.

Please note that Content AddOn packages of version 22.1 or newer can only be displayed correctly on agents with version 22.1.4 or later.

It is also guaranteed that older DriveLock Enterprise Services (DES) will not receive the new packages.

Additionally, the agents must have Microsoft Edge WebView2 installed. Please follow the download link: <https://developer.microsoft.com/en-us/microsoft-edge/webview2/#download-section>

Windows 11 already has Microsoft Edge WebView2 installed automatically.

 Note: This release does not contain any other bug fixes or improvements.

#### 4.1.2 Bug fixes 2022.1 HF1

DriveLock 2022.1 HF1 is a maintenance release.

This chapter contains information about issues that are fixed with DriveLock version 2022.1 HF1. Our External Issue numbers (EI) serve as references, where applicable.

| Reference | Application Control                              |
|-----------|--------------------------------------------------|
|           | Temporary unlocking is now terminated correctly. |

|         | BitLocker To Go                                                  |
|---------|------------------------------------------------------------------|
| EI-2037 | User dialogs are now also displayed in other languages than Eng- |

|  | <b>BitLocker To Go</b> |
|--|------------------------|
|  | lish.                  |

|         | <b>Device Control</b>                                                                                                                                        |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-2041 | We improved the evaluation of the device collections.                                                                                                        |
| EI-2039 | Fixed the timing issues with some devices.                                                                                                                   |
| EI-2002 | Bluetooth devices were not available with the Marvell AVASTAR wireless chip if the WiFi device was disabled during boot. The issue is fixed after rebooting. |

| <b>Reference</b> | <b>DriveLock Agent</b>                                                           |
|------------------|----------------------------------------------------------------------------------|
| EI-2053          | The autoupdate now also works when the agent's non-exit mode is enabled.         |
| EI-2036          | The DriveLock Service can now handle multiple remote connections simultaneously. |

| <b>Reference</b> | <b>DriveLock Management Console (DMC)</b>                                                                                                                                                              |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1994          | When editing and publishing the permanent unlock policy in the DMC, an incorrect policy type was entered, causing it to appear in the list of common policies. Now it is displayed in the right place. |

| Reference | DriveLock Operations Center (DOC)                                                                               |
|-----------|-----------------------------------------------------------------------------------------------------------------|
| EI-2045   | Temporary unlock in the DOC now displays an error if a weak code is used and the password or code is incorrect. |
| EI-2014   | Logging in to DOC now has no restrictions, the AD access issues have been resolved.                             |
|           | The list of application rules in the DOC showed only 20 rules. Now the number is no longer limited.             |

| Reference | Encryption-2-Go                                                                  |
|-----------|----------------------------------------------------------------------------------|
| EI-2003   | Encryption 2-Go can now also mount another container in Citrix Terminal Servers. |

| Reference | System Management                             |
|-----------|-----------------------------------------------|
|           | ZLib is now available in the current version. |

### 4.1.3 Bug fixes 2022.1

This chapter contains information about issues that are fixed with DriveLock version 2022.1. Our External Issue numbers (EI) serve as references, where applicable.

| Reference | Application Control                                                                                                 |
|-----------|---------------------------------------------------------------------------------------------------------------------|
|           | The Windows kernel occasionally deadlocked when Application Control attempted to access information from a process. |

| Reference | Application Control                                                                                                                       |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1863   | Some unusual behavior of third-party software might cause a stack overflow in the application control driver, resulting in a blue screen. |
|           | Deleting directories with a large number of files from the local whitelist took a long time and caused timeouts.                          |

| Reference | BitLocker Management / BitLocker To Go                                                                                                                                                                                                                                       |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | When taking over existing BitLocker environments, an error occurred on data drives for which auto unlock had been set.                                                                                                                                                       |
| EI-1669   | When encryption was performed only after a user had successfully logged in to the DriveLock PBA, the information dialog for the PBA was incorrectly displayed a second time.                                                                                                 |
| EI-1819   | In some cases, data partitions were encrypted with BitLocker only after a reboot.                                                                                                                                                                                            |
| EI-1769   | Fixed an issue that occurred after encrypting a USB stick with BitLocker To Go; the old password was not accepted in some cases when attempting to change the BitLocker management password.                                                                                 |
| EI-1809   | Fixed an issue where the BitLocker key backup failed on rare occasions; this meant that the BitLocker recovery key had to be entered in addition to logging in to the DriveLock PBA. Now encryption is started only after the BitLocker key has been successfully backed up. |

| Reference | BitLocker Management / BitLocker To Go                                                                   |
|-----------|----------------------------------------------------------------------------------------------------------|
| EI-1871   | The option for online password recovery, which is not available with BitLocker To Go, has been disabled. |

| Reference | Device Control                                                                                                    |
|-----------|-------------------------------------------------------------------------------------------------------------------|
| EI-1715   | The device control driver was still active even though the device control license had been removed from an agent. |

| Reference | Disk Protection                                                                     |
|-----------|-------------------------------------------------------------------------------------|
| EI-1741   | The Disk Protection status was not displayed correctly during and after decryption. |
| EI-1718   | Fixed issues with creating a Windows PE recovery medium.                            |

| Reference | DriveLock Agent                                                                                                                          |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1735   | The current Windows event logs were not used if the trace files of an agent were retrieved several times.                                |
| EI-1828   | If an agent cannot communicate with the server, a corresponding event is now generated only after the last attempt to communicate again. |
| EI-1632   | If users were found to have more than 700 group memberships, these memberships were not considered when evaluating the                   |

| Reference | DriveLock Agent                                                                                                                                                                               |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | drive rules.                                                                                                                                                                                  |
| EI-1820   | The automatic agent update process got delayed for a long time when the randomization of the update time was activated.                                                                       |
| EI-1713   | Reinstalling the DriveLock Agent MSI with the server connection settings now overwrites the previous settings.                                                                                |
| EI-1870   | In Windows 10 1809 and LTSC version 2019, DriveLock failed to work if the regional settings did not match the operating system language (e.g. English Windows with German regional settings). |
| EI-1830   | The agent service crashed in rare cases when terminated.                                                                                                                                      |
| EI-1672   | Fixed an issue where the temporary unlock ended before the set time in rare cases.                                                                                                            |
| EI-1757   | The tray icon process crashed when dialogs were opened multiple times, such as Agent Status dialog.                                                                                           |
| EI-1676   | Sometimes a change of the logged on user was only handled on the next policy update.                                                                                                          |

| Reference | DriveLock Enterprise Service (DES)                                                                                                                              |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1754   | The spelling of the tenant name on the agent must be case-insensitive. This is now also the case if the agent is connected to the central DES via a linked DES. |

| Reference | DriveLock Enterprise Service (DES)                                                                                                                                                                                                                                                                       |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1907   | Fixed an issue with saving the database backup path. Please check and correct the path (DriveLock Management Console -> DriveLock Enterprise Services -> Server -> DES -> Properties -> Scheduled Tasks -> Path for backup copies). Please note that the path must be entered as seen by the SQL server. |

| Reference | DriveLock Linux Agent                                                                           |
|-----------|-------------------------------------------------------------------------------------------------|
| EI-1821   | On IgelOS, the DriveLock Linux Agent can not reset/disconnect USB drives during policy updates. |
|           | The Linux Agent now handles Unicode characters correctly.                                       |

| Reference | DriveLock Management Console                                                                                                                                                            |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1892   | The Generate Report... context menu option returned an empty result in a GPO policy.                                                                                                    |
| EI-1864   | When editing a serial number in a whitelist rule, the error message "The serial number is already contained in the list" was displayed by mistake.                                      |
| EI-1781   | The DMC crashed when trying to edit the "Available drive letters for mounting encrypted drives" setting.                                                                                |
|           | The scripts for event responses were truncated after 4096 characters without informing the user. Now the user is informed accordingly. When using policies in JSON format, up to 30,000 |

| Reference | DriveLock Management Console                                                                                                      |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------|
|           | characters are now also possible.                                                                                                 |
| EI-1854   | The computer list in the Agent Remote Control node is now filtered based on defined permissions.                                  |
| EI-1941   | When loading a policy, the system sometimes crashed if the user did not have read permission on one or more nodes below Defender. |

| Reference | DriveLock Operations Center (DOC)                                                                                                                                                   |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1815   | Logging in to the DOC is now also possible if the user is a member of the "Protected users" group.                                                                                  |
| EI-1834   | If you wanted to edit a policy from the DOC, you also had to have the DMC installed to be able to see the list for selecting an agent in a whitelist rule. This issue is now fixed. |
|           | The DOC incorrectly indicated an active PBA on unencrypted systems.                                                                                                                 |
| EI-1880   | The drive activities for locked and allowed drives are now displayed correctly.                                                                                                     |
|           | When creating a group, you can now also add the appropriate group description.                                                                                                      |

| Reference | DriveLock pre-boot authentication                                                                                                                     |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1800   | Fixed an issue where a logged-in Windows user was not synchronized with the PBA in some cases after the first Windows logon after installing the PBA. |

| Reference | File Protection                                                                                     |
|-----------|-----------------------------------------------------------------------------------------------------|
| EI-1381   | Fixed an issue that caused data corruption in large Excel files after changes and "Save / Save as". |

|         | Inventory                                                                                                                                                                                                                              |
|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1742 | You had to activate the Enable collecting inventory data option in the Policy Editor inventory settings (Hardware and Software Inventory) so that the OS name/version were displayed in the DOC. Now this option is set automatically. |

| Reference | Security Awareness                                                                                          |
|-----------|-------------------------------------------------------------------------------------------------------------|
| EI-1791   | Retrieving executed campaigns from the DES only worked if the campaigns had already been executed at login. |

| Reference | Terminal Services                                                                                                        |
|-----------|--------------------------------------------------------------------------------------------------------------------------|
| EI-1497   | Portable media devices (like cameras, media players) are now controlled in Terminal Services environments when connected |

---

| Reference | Terminal Services                                    |
|-----------|------------------------------------------------------|
|           | through a terminal session (in ICA or RDP protocol). |

## 4.2 Version 2021.2

### 4.2.1 Bug fixes 2021.2

This chapter contains information about errors that are fixed with DriveLock version 2021.2. Our External Issue numbers (EI) serve as references, where applicable.

| Reference | BitLocker Management / DriveLock PBA                                                                                                                                                                    |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1594   | A timeout in the BLM recovery wizard is now avoided if there are too many recovery information entries in the DES database                                                                              |
| EI-1663   | When assigning a policy without a valid BitLocker Management license, it was possible that systems that were already encrypted were decrypted again and any DriveLock PBA that was present was removed. |
| EI-1386   | If control panel items were already hidden via corresponding registry entries, they were displayed again as soon as BitLocker Management was enabled via a policy.                                      |
|           | If the authorization type in the policy was changed from 'Password' to 'DriveLock-PBA', the emergency credentials were not uploaded to the DES or were uploaded after the next reboot.                  |
| EI-1396   | When taking over existing BitLocker environments, it was possible that the new password to be assigned was requested twice.                                                                             |
|           | If the automatic unlocking of data drives was disabled, it was not possible to change passwords via the agent while the respective data drives were locked.                                             |
| EI-1431   | The BitLocker encryption was started without waiting for the recovery data to be successfully transferred to the DES.                                                                                   |

| Reference | BitLocker Management / DriveLock PBA                                                                                                                  |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1616   | If there is no DES available when the drive status is determined, no further attempt was made to upload it.                                           |
|           | In some cases, the emergency logon to the DriveLock PBA was not possible if the upload of the data failed because of a missing connection to the DES. |
|           | In some cases, USB drives encrypted with BitLocker blocked the Disk Protection installation.                                                          |

| Reference | Defender Management                                                                                                                                                                                             |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | Fixed an issue related to switching the scan type of Windows Defender.                                                                                                                                          |
| EI-1485   | In some cases, the agent incorrectly reported that Microsoft Defender was disabled (Defender Event 698: "Microsoft Defender is disabled"). This issue is now fixed.                                             |
| EI-1644   | The agent now immediately reports a successful update of the Defender signature to the DES. Previously, this information was sent only once a day and an outdated signature was sometimes displayed in the DOC. |

| Reference | Device Control                                                            |
|-----------|---------------------------------------------------------------------------|
| EI-1578   | You can now create device collections for Apple devices in the DMC again. |

| Reference | Device Control                                                                                                                          |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------|
| EI-1626   | Processes that are globally excluded from shadowing, reporting and filtering are now added to the excluded process list of the DLFsFlt. |
| EI-1436   | Shadow files were created during CD burning, even if shadow files were disabled in the corresponding filters.                           |
|           | In the Devices node, the scroll bar was missing in the Taskpad view of the Management Console.                                          |

| Reference | Disk Protection                                            |
|-----------|------------------------------------------------------------|
| EI-1730   | The dlfi.exe tool now works in the Windows PE environment. |

| Reference | DriveLock Agent                                                                                                                                  |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------|
|           | Fixed an error that prevented remote unlocking of another computer when using self-service unlocking on agents connected to a linked DES server. |
| EI-1645   | Fixed a performance issue that occurred when a USB flash drive was inserted while the agent was running in simulation mode.                      |
| EI-1501   | In certain configurations, event 461 was sent by mistake when the schedule had been set to "At system startup". This issue is fixed now.         |

| Reference | DriveLock Agent                                                                                                                                              |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1540   | The agent interface now displays the correct policy status when Group Policy Objects (GPOs) are used.                                                        |
| EI-1622   | DriveLock.exe now supports command line calls (with -ArgumentList) from the " Start-Process" call of Powershell.                                             |
| EI-1518   | When another user logged in, DriveLock no longer responded when a CD burner was present.                                                                     |
| EI-1569   | Certain file exclusions in file filters did not work.                                                                                                        |
| EI-1682   | On certain Lenovo computers, the agent crashed while collecting encryption information from the drives. This issue is now fixed.                             |
| EI-1618   | If a client switched to a different DES due to a change in network location, the MQTT connection continued to use the previous DES. This issue is fixed now. |
| EI-1558   | Creating a bootable USB drive with Rufus failed or took a long time because it was blocked by the DriveLock agent.                                           |

| Reference | DriveLock Enterprise Service (DES)                                                                                                                        |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1532   | Fixed an issue with excessive CPU load on linked DES. This sometimes happened when the linked DES could not access ports 4568 or 8883 on the central DES. |
|           | Fixed an issue that caused handle leaks in DES.                                                                                                           |

| Reference | DriveLock Operations Center (DOC)                                                                                                                                                            |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1384   | Requesting the Bitlocker recovery key via the DOC now causes the recovery key to be renewed on the agent and no longer requires the old password in the password change dialog on the agent. |
| EI-1498   | The value in the Encryption or decryption in progress widget is now displayed correctly.                                                                                                     |

| Reference | EDR/Events                                                                           |
|-----------|--------------------------------------------------------------------------------------|
|           | Changing the display texts of 3rd party event sources was not saved in the database. |
|           | Improved the display of the names of event parameters in the DMC.                    |

|         | File Protection                                                                                                                                                               |
|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-356  | When a user's permissions were set to Read Only in the Centrally managed folders node, they were changed back to Write when the dialog was reopened. This issue is fixed now. |
| EI-1664 | The File Protection node in the policy also contains settings needed for Encryption 2-Go. Still, the node was not available with just an Encryption 2-Go license.             |
| EI-1068 | Fixed an issue with opening, changing and saving an Office Document in an encrypted folder in mounted network shares.                                                         |

|         | <b>File Protection</b>                                                                                                                             |
|---------|----------------------------------------------------------------------------------------------------------------------------------------------------|
|         | Fixed the bluescreen that occurred when accessing a mounted encrypted folder in a computer with DriveLock from another computer without DriveLock. |
| EI-1543 | Fixed an issue that could result in corrupted Excel files when opened from an encrypted folder.                                                    |
| EI-1562 | File Protection now works correctly with password-protected Excel files.                                                                           |
| EI-1574 | Some File Protection events were not logged. This issue is fixed now.                                                                              |

| <b>Reference</b> | <b>Security Awareness</b>                                                           |
|------------------|-------------------------------------------------------------------------------------|
| EI-1614          | The Security Awareness Library is now only opened in the user's respective session. |

## 4.3 Version 2021.1

### 4.3.1 Bug fixes 2021.1 HF1

DriveLock 2021.1 HF1 is a maintenance release.

This chapter contains information about errors that are fixed with DriveLock version 2021.1 HF1. Our External Issue numbers (EI) serve as references, where applicable.

| Reference | DriveLock Agent                                                                                                                                                                                                                       |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1517   | If the "Allow authorized user login" option was manually set on the Awareness tab when specifying usage policies, this option was not considered during evaluation (the behavior was the same as if the option had not been checked). |
| EI-1534   | Fixed the performance issue.                                                                                                                                                                                                          |

|                          | File Protection                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| EI-387, EI-1086, EI-1148 | Fixed a permissions issue that required full control over network shares. (The same applies to all associated EIs). |

| Reference | DriveLock Management Console                                                                                                                                                                                                               |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1516   | After upgrading to DriveLock 2021.1, the client compliance and hardware and software inventory options could not be configured if there was no license for Vulnerability Scanner (although these features should not depend on a license). |

### 4.3.2 Bug fixes 2021.1

This chapter contains information about errors that are fixed with DriveLock version 2021.1. Our External Issue numbers (EI) serve as references, where applicable.

| Reference | BitLocker Management                                                                                                                                                                                                                                                                  |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | <p>The configuration of BitLocker password complexity was not saved correctly if you first applied a complexity setting and then disabled password complexity.</p>                                                                                                                    |
|           | <p>The password for data partitions was changed twice if the password for the system partition was changed at the same time. Thus, when taking over existing BitLocker environments, an error could occur whereby individual data partitions were only taken over after a reboot.</p> |
| EI-1312   | <p>An existing configuration for backing up BitLocker recovery keys in Active Directory was overwritten after installing DriveLock in such a way that backing up was no longer possible afterwards.</p>                                                                               |
| EI-1388   | <p>Taking over existing BitLocker environments failed in some cases for partitions where only one protector was present.</p>                                                                                                                                                          |
|           | <p>Taking over BitLocker-encrypted systems failed if no protectors were present. Under certain conditions, system and data partitions are pre-encrypted with BitLocker after Windows 10 is installed without any protectors being created.</p>                                        |
| EI-1342   | <p>With certain settings in Windows Group Policy, the BitLocker password of data partitions could not be set by BitLocker Management.</p>                                                                                                                                             |
| EI-1337   | <p>Fixed an issue that prevented BitLocker from changing the pre-boot authentication type. This only affected systems that did not require re-encryption.</p>                                                                                                                         |
|           | <p>Terminating the agent service was significantly delayed by the BitLocker Management component. In some cases, this could also lead to the service crashing.</p>                                                                                                                    |
|           | <p>When the options to pause BitLocker encryption were set in the policy, encryption continued even if the event occurred.</p>                                                                                                                                                        |

| Reference                    | BitLocker Management                                                                                                                                                                                                                                    |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                              | <p>When taking over existing BitLocker environments with at least one locked data partition, you could click the unlock button again even after the unlock operation had already been completed. Thus, you could not terminate the wizard any more.</p> |
| EI-1395, EI-1396,<br>EI-1416 | <p>When taking over BitLocker-encrypted drives, the password was prompted twice if both the system protector and the encryption algorithm had to be changed.</p>                                                                                        |
| EI-1418                      | <p>If the control panel was restricted to certain items via a system policy, this setting was overwritten as soon as DriveLock BitLocker Management was enabled.</p>                                                                                    |
| EI-1464                      | <p>If the license for BitLocker Management was missing, it was possible that a previously encrypted system was decrypted even though the 'Do not decrypt on configuration changes' setting had been specified.</p>                                      |

| Reference | Defender Management                                                                                                                                                                                                         |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | <p>Once the dialog for delaying the start of the Defender scan had been displayed, the DriveLock service could no longer be terminated.</p>                                                                                 |
|           | <p>The dialog for delaying the start of the Defender scan appeared even though a delay was not configured.</p>                                                                                                              |
|           | <p>The display of files in quarantine on the Defender tab of the Agent remote control dialog contained incorrect and truncated entries. Außerdem war nur ein Teil des Textes sichtbar, da der Tooltip-Text gefehlt hat.</p> |

| Reference                 | Device Control                                                                                        |
|---------------------------|-------------------------------------------------------------------------------------------------------|
| EI-1323, EI-1336, EI-1341 | File definitions for multiple file types were processed incorrectly by the file filter.               |
| EI-1220                   | Fixed an issue that occurred when processing custom messages when locking iPhone and Android devices. |
| EI-1294                   | Drive rules have a priority order now.                                                                |

| Reference | DriveLock Agent                                                                                                                                                                                                                                                                                                                                                                             |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1321   | <p>Sometimes it was not possible to run an action on the agent when the MMC and the DOC were started at the same time and used for agent remote control.</p> <p>If a user was logged on to Windows who did not have permissions for agent remote control, it was not possible to use agent remote control from the DOC, even if the user logged on to the DOC had permissions to do so.</p> |

| Reference | DriveLock Enterprise Service (DES)                                                                        |
|-----------|-----------------------------------------------------------------------------------------------------------|
| EI-1302   | The DriveLock Enterprise Service Setup allows users to be selected from a different trusted forest model. |
| EI-1355   | Fixed an issue that caused the DES to crash when a computer was deleted.                                  |

| Reference | DriveLock Pre-Boot Authentication                                                                                        |
|-----------|--------------------------------------------------------------------------------------------------------------------------|
|           | Emergency logon data was not uploaded if the system partition was not encrypted but the DriveLock PBA was supposed to be |

| Reference | DriveLock Pre-Boot Authentication                                                                                                                                                                                                                                                                                                  |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | installed.                                                                                                                                                                                                                                                                                                                         |
|           | In the case where only data partitions were encrypted and not the system partition with DriveLock PBA enabled, the password for the data partitions was not requested. However, this password is needed because in this case data partitions are not unlocked automatically and manual unlocking with a user password is required. |
|           | For drives pre-encrypted with BitLocker, the DriveLock PBA installation started and finished with an error.                                                                                                                                                                                                                        |
| EI-1243   | After activating the network PBA, the system drive was decrypted and then re-encrypted even though the DriveLock PBA was already set up.                                                                                                                                                                                           |
| EI-1287   | When using Windows Quick Start, data partitions were no longer automatically unlocked after startup. In environments where the DriveLock PBA was configured, the BitLocker recovery key was required for unlocking.                                                                                                                |

| Reference | EDR/Events                                                                                                                                             |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | In the text for event 635, the error code to isolate the error was missing. The event provides information that the BitLocker password setting failed. |
|           | Fixed an issue where saving a new alert category to a centrally stored policy failed.                                                                  |

| Reference | Encryption-2-Go                                         |
|-----------|---------------------------------------------------------|
| EI-1212   | Handling incomplete recovery information was corrected. |

|         | <b>File Protection</b>                                                                   |
|---------|------------------------------------------------------------------------------------------|
| EI-1259 | Fixed an issue with a BSOD in the Terminal Server environment.                           |
| EI-1163 | Fixed an issue where copying XML files to SMB 3.0 cluster shares corrupted the XML file. |

| <b>Reference</b> | <b>Configuration (policies)</b>                                                                                                                                                                     |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-376           | Users were not informed that they had selected the insecure HTTP protocol in the server configuration.                                                                                              |
| EI-1346          | Improved AD information caching. Even if no AD information is available, DriveLock groups and assignments of centrally stored policies can be used as long as they do not depend on AD information. |
|                  | Some settings were not applied correctly when saving or exporting a local policy. This issue is fixed now.                                                                                          |

| <b>Reference</b> | <b>Licensing</b>                                                        |
|------------------|-------------------------------------------------------------------------|
| EI-1150          | License activation in the MMC now also works when using a proxy server. |

| <b>Reference</b> | <b>System Management</b>                                                                                                                                                                                                                     |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1307          | When available, the network name of the computer is now returned by the agent as FQDN and the NetBIOS name is only used if there is no FQDN. This makes agent remote control more stable, since it can also find computers in other domains. |

## 4.4 Version 2020.2

### 4.4.1 Bug fixes 2020.2

This chapter contains information about errors that are fixed with DriveLock version 2020.2. Our External Issue numbers (EI) serve as references, where applicable.

| Reference                 | Device Control                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1228, EI-1235, EI-1236 | The definition of Office file formats has been extended based on the respective specification.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| EI-1220                   | The custom message is now displayed instead of the default message when an Apple device has been blocked by a base rule.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|                           | Fixed a bug in the DriveLock file system filter driver that caused a BSOD when inserting a USB stick.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| EI-1188                   | <p>It is now possible to access the memory card in a digital camera connected to the Fat Client or Thin Client with a USB cable if the <code>MtpRestartTimeout (REG_DWORD) (REG_DWORD)</code> value in the registry key <code>HKEY_LOCAL_MACHINE\SOFTWARE\CenterTools\DLSettings\Devices</code> is set to 3000 (ms).</p> <div data-bbox="424 1413 1394 1547" style="border: 1px solid #add8e6; padding: 5px;"> <p> Note: Since Windows 10 Update 2020, the camera may only be accessed if the Generic virtual channel is set in the Citrix Workspace.</p> </div> |
| EI-1230                   | A blue screen sometimes occurred after connecting a USB stick. This bug is fixed now.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

| Reference | Disk Protection                                                                                                                                                                                                                                                                                                                                                |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | <p>The uninstallation of the DriveLock Agent will abort if DriveLock Disk Protection is installed on the system. The user will see a corresponding message that DriveLock Disk Protection must be uninstalled before the DriveLock Agent can be uninstalled. Up to now, the DriveLock Agent uninstallation failed without any error messages in this case.</p> |

| Reference | DriveLock Agent                                                                                                                                                                        |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1137   | Fixed an issue where DriveLock blocked Google drives.                                                                                                                                  |
| EI-815    | In the Application Whitelist display, a column has been added to show the hash of each file to get a better overview.                                                                  |
| EI-769    | Fixed a bug where Japanese could be selected as the language for the agent user interface. Japanese is no longer supported.                                                            |
| EI-1179   | Changing the network location did not immediately reconfigure MQTT. As a result, at times the agent could not be reached via agent remote control.                                     |
| EI-1179   | When switching between different DES servers, agents could temporarily not be reached via MQTT because they received the wrong server certificate for MQTT communication from the DES. |
| EI-1065   | Filters on AD groups and AD OUs sometimes only worked correctly if there was a connection to the AD.                                                                                   |

| Reference                               | DriveLock Agent                                                                                                                                                                                                                        |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EIs: 1066, 1075, 1080, 1090, 1116, 1156 | A number of improvements have been made to the update mechanism.                                                                                                                                                                       |
| EI-1182                                 | Agent remote control via the DES sometimes failed if the agent was connected to a Linked DES and remote control was only possible via MQTT. This happened when the user running the Linked DES did not have rights on the central DES. |
| EI-932                                  | Fixed a bug where a Drivelock Agent installed with unstopable mode sometimes ended up in an inconsistent state.                                                                                                                        |

| Reference                          | DriveLock Control Center (DCC)                                                            |
|------------------------------------|-------------------------------------------------------------------------------------------|
| EI-1068, EI-1069, EI-1091, EI-1076 | In DCC, the ConfigID column now displays the policy name and version instead of the GUID. |

| Reference | DriveLock Enterprise Service (DES)                                                                                                                                                                     |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | Up to now, it was possible to run DriveLock Enterprise Setup without providing a certificate. This bug is fixed now. You must either select a certificate or explicitly specify to generate a new one. |
| EI-1095   | The password for the DES user can now contain a semicolon. Previously, such passwords caused the DES setup to abort.                                                                                   |
| EI-1122   | Fixed an issue when adding licensed computers to the server.                                                                                                                                           |

| Reference | DriveLock Enterprise Service (DES)                                                                               |
|-----------|------------------------------------------------------------------------------------------------------------------|
| EI-1097   | The description (AD) of the computer is now saved correctly in the inventory.                                    |
| EI-1197   | Fixed a bug when configuring policy assignments to very long OU names.                                           |
| EI-1171   | The Database Installation Wizard now detects the configured Client SecurityProtocol settings (TLS).              |
| EI-1246   | The database installation wizard now recognizes settings from linked DES and makes the appropriate preselection. |
| EI-1164   | Fixed an issue regarding the evaluation of the certificate revocation list.                                      |
| EI-1202   | Improved performance when processing AgentAlives (agent status message) and when saving events.                  |

| Reference        | File Protection                                                                                                   |
|------------------|-------------------------------------------------------------------------------------------------------------------|
| EI-1216          | Fixed an issue where a service (DLFFEGui) would crash when decrypting encrypted folders. This issue is fixed now. |
| EI-1143, EI-1163 | While mounting an encrypted folder, the service for re-encrypting unencrypted files no longer starts.             |

| Reference | DriveLock Management Console                                                                                                                                                                                           |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1049   | The DMC sometimes displayed computers with the name of the previous entry in the Agent remote control node.                                                                                                            |
| EI-1150   | Fixed a bug with license activation via proxy in the DMC. The DMC uses proxy settings that are set via Internet Explorer. The proxy entered via the DriveLock command <code>setproxy</code> is not taken into account. |
| EI-1133   | While saving a GPO, an error sometimes occurred that a path could not be found.                                                                                                                                        |
| EI-1135   | When saving a GPO, an error sometimes occurred that the caller did not have sufficient rights.                                                                                                                         |
| EI-1151   | While working in the DriveLock File Protection node, the root tenant was always preselected in some dialogs instead of the tenant that was actually being used.                                                        |

| Reference | DriveLock Operations Center (DOC)                                                                                                            |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------|
|           | You can reset filters set via a context menu command only in the main view. In other views you need to click 'Refresh' to reset the filters. |

| Reference                          | DriveLock Pre-Boot Authentication                                                     |
|------------------------------------|---------------------------------------------------------------------------------------|
| Els: 1103, 1106, 1110, 1138, 1160, | A workaround has been implemented for some issues with internal keyboards in the PBA. |

| Reference  | DriveLock Pre-Boot Authentication                                                                                                                                              |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1170, 1178 |                                                                                                                                                                                |
| EI-1218    | Single sign-on via DriveLock PBA failed when a user's password was changed outside DriveLock and SafeGuard file encryption (credential provider) was also present on a system. |

| Reference | EDR                                                                                                                            |
|-----------|--------------------------------------------------------------------------------------------------------------------------------|
| EI-1241   | The events, which were generated when no connection to the DES was possible, were not sent to the DES afterwards in all cases. |
| EI-1240   | Event 257 (file deleted) was not generated in all cases.                                                                       |
| EI-1154   | Fixed an issue in the wording of event 474.                                                                                    |

| Reference | Encryption-2-Go                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1204   | <p>Since Windows 10, Windows notifies a user unlock as a new logon and not as an unlock. In conjunction with the DriveLock PBA and Enc2Go, for example, this cancels a backup that is currently running. In order to identify an unlock as a user unlock again, you have to set the following GPO:</p> <p>Windows Registry Editor Version 5.00</p> <ul style="list-style-type: none"> <li>• ; Computer Configuration -&gt; Windows Settings -&gt; Security Settings -&gt;</li> </ul> |

| Reference | Encryption-2-Go                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | <ul style="list-style-type: none"> <li>• ; Local Policies -&gt; Security Options "Interactive logon: Do not display last user name"</li> <li>• ; Set to "Enabled": asks to unlock the machine only to currently logged user</li> <li>• ; <a href="https://docs.microsoft.com/en-us/windows/security/threat-protection/security-policy-settings/interactive-logon-do-not-display-last-user-name">https://docs.microsoft.com/en-us/windows/security/threat-protection/security-policy-settings/interactive-logon-do-not-display-last-user-name</a></li> <li>• [HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\Policies\System]</li> <li>• "dontdisplaylastusername"=dword:00000001</li> </ul> |

|                  | File Protection                                                                                                                           |
|------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1146          | The memory loss has been fixed.                                                                                                           |
|                  | The code has been extended to allow copy/move to root share.                                                                              |
| EI-1111; EI-1279 | Sophos SAVSERVICE.EXE is handled as a backup app.                                                                                         |
| EI-1159          | When shutting down the computer, the FFE driver could not always be removed because Windows terminated the DriveLock service prematurely. |
| EI-1143          | Fixed an issue with copying Outlook messages to the network.                                                                              |

| Reference | Configuration (policies)                                                                                                         |
|-----------|----------------------------------------------------------------------------------------------------------------------------------|
| EI-1005   | Now, the agent no longer evaluates Group Policy Objects if there are centrally stored policies or configuration files available. |

| Reference | Licensing                                                                                                                                                   |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1192   | In the File Protection trial license provided, the number of File Protection licenses was 0 instead of 10.                                                  |
| EI-1099   | Even with a valid license, a warning was briefly displayed when you opened a policy in the DMC indicating that you were "only" working with a test license. |

| Reference | Security Awareness                                                                                                         |
|-----------|----------------------------------------------------------------------------------------------------------------------------|
| EI-1057   | The Security Awareness view in DriveLock Operations Center (DOC) is now always displayed, regardless of the license check. |

## 4.5 Version 2020.1

### 4.5.1 Bug fixes 2020.1

This chapter contains information about errors that are fixed in DriveLock version 2020.1. Our External Issue numbers (EI) serve as references, where applicable.

| Reference       | BitLocker Management / DriveLock Pre-Boot Authentication                                                                                                               |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-891          | In the overview for hard disk encryption, you found that Pre-Boot Authentication was shown as disabled even though the BitLocker PBA option was selected.              |
| EI-872 , EI-989 | Whenever possible, the firmware keyboard driver is now replaced by a newer driver that supports layouts.                                                               |
| EI-946          | The credential provider for the NetIQ Client Login Extension did not work correctly with DriveLock on Windows 10. Users were not added to the Pre-Boot Authentication. |

| Reference | Device Control                                                                                                              |
|-----------|-----------------------------------------------------------------------------------------------------------------------------|
| EI-453    | When adding a new file type definition, a false warning appeared that a file type definition already existed for this type. |
| EI-819    | Drive and device collections were no longer stored in the policy and thus could not be used any more.                       |
| EI-540    | Burning devices are now more easily identified and burning is enabled for users with write access to CD/DVD-ROM.            |
| EI-776    | The MTP driver dependencies that prevented the MTP driver from loading have been removed.                                   |

| Reference | Device Control                                                                         |
|-----------|----------------------------------------------------------------------------------------|
| EI-859    | A misleading message regarding the release status of an iPhone is no longer displayed. |

| Reference | Disk Protection                                                                                                                                                                                                                                         |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-915    | A new PS2 combined keyboard/mouse driver replaces keyboard drivers. The splash screen has been adjusted. Keyboard layout list shortened and re-sorted. ESC key now not only closes open menus, but also activates the F1 key function (password login). |
| EI-756    | Corrected the SSO data transfer behavior (BSOD) on several Dell notebooks.                                                                                                                                                                              |
| EI-995    | SSO for token logon is defined in DriveLock Credential Provider.                                                                                                                                                                                        |
| EI-914    | If a license was removed from a Disk Protection or BitLocker management policy that requires separate installation steps and these steps have already been performed, DriveLock Agent displayed incorrect behavior. This bug is fixed now.              |

| Reference | DriveLock Control Center (DCC)                                                                                       |
|-----------|----------------------------------------------------------------------------------------------------------------------|
| EI-721    | Fixed an error in the display of the license information.                                                            |
| EI-997    | Fixed an error when loading the DCC helpdesk, that occurred with a large number of computers with FDE recovery data. |

| Reference | DriveLock Control Center (DCC)                                                                                              |
|-----------|-----------------------------------------------------------------------------------------------------------------------------|
| EI-749    | In the DCC Helpdesk, it was not possible to connect to an agent in a filtered list if the agent did not appear in the list. |

| Reference              | DriveLock Enterprise Service (DES)                                                                                                                                       |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-896                 | The ChangeDesCert utility now also works correctly if a certificate was selected several times in a row with the menu command "Select".                                  |
| EI-931                 | The DES (MQTT) will no longer attempt to listen to port 8083 and 8084. To reduce conflicts, port 18082 is now used instead of port 8080. This port is only used locally. |
| EI-977                 | Caching improves the performance when the agent on the DES requests configuration settings for agent remote control (MQTT).                                              |
| EI-773, EI-998, EI-754 | Improved performance of DES (alive and event processing)                                                                                                                 |
| EI-1024, EI-977        | Fixed the error in the DES or MQTT configuration that caused increased load on the DES computer.                                                                         |
| EI-874                 | Fixed the error in the DES that resulted in significantly increased memory consumption when listing many policies.                                                       |
| EI-937                 | Fixed an error when processing file access events with long path names.                                                                                                  |

| Reference | DriveLock Operations Center (DOC)                                                                                                   |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------|
| EI-907    | The DOC now allows login of users from child domains and domains linked via Forest Trust.                                           |
| EI-922    | The menu command to start the DOC from the DCC now works even if the DES server has a very long FQDN (fully qualified domain name). |
| EI-1000   | You can solve the issue by using Microsoft Edge version 81.0.416.64 (official build) (64-bit).                                      |
| EI-1006   | It is now possible to group DriveLock agents by means of the Disk Encryption Status property.                                       |

| Reference | Encryption-2-Go                                                                                                                    |
|-----------|------------------------------------------------------------------------------------------------------------------------------------|
| EI-506    | DriveLock Mobile Encryption (Encryption-2-Go and File Protection) can now be used on Apple OS X and Mac OS X without restrictions. |
| EI-761    | Version 2020.1 includes a workaround for FAT 32 which solves the described issue.                                                  |

| Reference      | File Protection                                                     |
|----------------|---------------------------------------------------------------------|
| EI-763, EI-767 | The driver was revised to solve potential synchronization problems. |

| Reference | File Protection                                                                                                               |
|-----------|-------------------------------------------------------------------------------------------------------------------------------|
| EI-941    | Fixed the issue related to downloading Office 365 files to encrypted folders with pathnames > 128 characters.                 |
| EI-825    | Replaced limiting static memory allocation by dynamic memory allocation in the driver to avoid problems with long file names. |
| EI-952    | The unmount required to delete an encrypted folder was completely unsynchronized. This is fixed now.                          |
| EI-953    | The unmount required to rename an encrypted folder was completely unsynchronized. This is fixed now.                          |
| EI-954    | The unmount required for decrypting was missing and is now performed.                                                         |
| EI-955    | The unmount required for copying and moving was missing and is now performed.                                                 |
| EI-956    | The settings for the shell extensions are now evaluated correctly.                                                            |
| EI-537    | Improved detection of centrally managed encrypted folders.                                                                    |
| EI-940    | The event variable CloudId, which was not initialized, is now initialized.                                                    |

| Reference | Configuration                                                                                             |
|-----------|-----------------------------------------------------------------------------------------------------------|
| EI-752    | The DriveLock Agent is now able to successfully work with policy configuration files (.cfg) on UNC paths. |
| EI-803    | It did not work to configure the system using the configuration file.                                     |
| EI-398    | Policies without license information could affect the license information.                                |

| Reference      | Management Console                                                                                                                     |
|----------------|----------------------------------------------------------------------------------------------------------------------------------------|
| EI-999, EI-990 | Loading the policy assignments in the Management Console was too slow.                                                                 |
| EI-827         | When adding new licenses in the Management Console, newly added modules were automatically activated for all computers.                |
| EI-719         | Text in the Management Console that was too long was simply cut off when previewing contact information for the Offline Unlock Wizard. |
| EI-864         | The Management Console now uses the proxy configured in the Internet Explorer settings for accessing the Internet.                     |

| Reference | Mobile Encryption                                          |
|-----------|------------------------------------------------------------|
| EI-643    | Improvements for the encryption driver were already imple- |

| Reference | Mobile Encryption                                                        |
|-----------|--------------------------------------------------------------------------|
|           | mented in version 2019.2.                                                |
| EI-639    | DriveLock MAC applications are no longer encrypted on Windows computers. |

| Reference | Self-Service                                                                                                                                                                                                                                                                                                                                                  |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-538    | Self-service on the agent is now terminated as configured when a user logs off in an RDP session.                                                                                                                                                                                                                                                             |
| EI-762    | The icons for the wizard banners must have a size of 49x49 pixels - since they were only 48x48 pixels before, white lines were added to the images.                                                                                                                                                                                                           |
| EI-724    | When using the Offline Unlock Wizard, you could jump to the next page even if you had not yet selected any modules to be unlocked.                                                                                                                                                                                                                            |
| EI-867    | The first time you reached the dialog page where you set the time for policy settings to be deactivated, the current time used to be specified. When moving back and forth one page, a time from the past would appear on the dialog page. Now, each time you access the page, the current time is entered, incremented by the maximum allowed unlock period. |
| EI-759    | In some cases, the temporary unlock of the agent failed with "Access to DriveLock agent denied".                                                                                                                                                                                                                                                              |
| EI-991    | The self-service unlock does not work on computers that have been identified by the OU.                                                                                                                                                                                                                                                                       |

| <b>Reference</b> | <b>Security Awareness</b>                                               |
|------------------|-------------------------------------------------------------------------|
| EI-810           | Built-in pictures of Security Awareness were only available in English. |

## 4.5.2 Bug fixes 2020.1 HF1

This chapter contains information about errors that are fixed with DriveLock version 2020.1 HF1.

Our External Issue numbers (EI) serve as reference, where applicable.

| Reference | Application Control                                                                                                                                                                                                  |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | If you selected the <b>Set to configured list</b> option in the <b>Directories learned for the local whitelist</b> dialog and excluded a folder, a blank entry appeared (blank entries or first characters missing). |
|           | Folders for application rules were only visible at the top level after restarting the MMC - subfolders at a lower level were still there but no longer visible.                                                      |

|         | Device Control                                                                                                               |
|---------|------------------------------------------------------------------------------------------------------------------------------|
| EI-1070 | In some configurations, a script was able to access a drive within milliseconds after it was mounted. This bug is fixed now. |

| Reference | DriveLock Control Center (DCC)                                   |
|-----------|------------------------------------------------------------------|
| EI-1055   | OU filters configured for users now also work for event reports. |

| Reference | DriveLock Enterprise Service (DES)                                                       |
|-----------|------------------------------------------------------------------------------------------|
|           | The DriveLock Service account no longer requires administrator rights on the Linked DES. |

| Reference | DriveLock Management Console                                                                                       |
|-----------|--------------------------------------------------------------------------------------------------------------------|
|           | The policy's tenant name is now submitted to prevent errors when reading drive information from the remote client. |

|  | DriveLock Operations Center (DOC)                                                                                                                             |
|--|---------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | Displaying a computer in the Computer Details view of the DOC did not work correctly (server error) if the OU name or path contained a single inverted comma. |

| Reference | DriveLock Pre-Boot Authentication                                                                                            |
|-----------|------------------------------------------------------------------------------------------------------------------------------|
|           | Error handling has been improved when installing DriveLock PBA.                                                              |
|           | When changing the logon methods for pre-boot authentication, the PBA was sometimes not installed correctly.                  |
| EI-1071   | Some MMC settings for the DriveLock PBA were not saved correctly. This affects the " User Synchronization" and "Users" tabs. |
|           | The bluescreen after PBA logon to the encrypted computer (Windows 10 2004 BIOS) no longer appears.                           |

| Reference | File Protection                                                                                                                                                                                                                                                                                                |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1053   | The "[DriveLock File Protection]" menu item can now be disabled via the DriveLock Agent's system tray icon.                                                                                                                                                                                                    |
| EI-1064   | File & Folder Encryption in combination with Full Disk Encryption may produce a bluescreen BugCheck 7F, {8, ...} after a Windows Inplace Upgrade. The Windows Inplace Upgrade changes the FFE driver load order. This is corrected during the first boot after the Upgrade, but the bluescreen may occur once. |

| Reference | Microsoft Defender                                                                                                                                                                       |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | When you set a specific day of the week for the Defender Scan, the next day of the week appeared (e.g. Friday instead of Thursday). However, the actual weekday was saved and evaluated. |

### 4.5.3 Bug fixes 2020.1 HF2

This chapter contains information about errors that are fixed with DriveLock version 2020.1 HF2.

Our External Issue numbers (EI) serve as reference, where applicable.

| Reference | DriveLock Pre-Boot Authentication                                                                                                     |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------|
|           | Fixed an issue where the user was prompted to enter a BitLocker recovery key in certain situations after logging in to DriveLock PBA. |

#### 4.5.4 Bug fixes 2020.1 HF3

This chapter contains information about errors that are fixed with DriveLock version 2020.1 HF3.

Our External Issue numbers (EI) serve as reference, where applicable.

| Reference        | DriveLock Agent                                                                                                                                                                      |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1147          | Improved access time to network shares when detailed information is not required.                                                                                                    |
| EI-1123          | Fixed an error related to using Agent remote control which occurred with Novell eDirectory.                                                                                          |
| EI-1084          | After retrieving the recovery key, it was not replaced in some cases after the reboot. If you had to enter a password after rebooting, the password dialog was not displayed either. |
| EI-1117, EI-1145 | The file system filter blocked too much.                                                                                                                                             |

| Reference | Application Control                                                                                                                                                                                     |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1124   | The <b>Trusted process (allow this executable as well as all child processes)</b> option was grayed out. It is now available again in the standard application control without predictive whitelisting. |

| Reference | BitLocker Management                                                                                                 |
|-----------|----------------------------------------------------------------------------------------------------------------------|
| EI-1100   | BitLocker Management could not automatically unlock data partitions after rebooting a computer with the Fast Startup |

| Reference | BitLocker Management                                                                   |
|-----------|----------------------------------------------------------------------------------------|
|           | option enabled in Windows 10.                                                          |
|           | The system drive password change failed for BitLocker-encrypted computers without TPM. |

| Reference | Device Control                                                                                                                       |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------|
| EI-1118   | The file system filter driver was changed to prevent blocking of devices.                                                            |
| EI-1155   | Improved detection of CD/DVD burners.                                                                                                |
| EI-1121   | The policy's tenant name is now sent with the policy so that no error occurs when reading device information from the remote client. |

| Reference | Encryption-2-Go                                                           |
|-----------|---------------------------------------------------------------------------|
| EI-1107   | The file system filter driver was changed to prevent blocking of devices. |

| Reference | DriveLock Enterprise Service (DES)                                                                                   |
|-----------|----------------------------------------------------------------------------------------------------------------------|
| EI-1095   | The password for the DES user can now contain a semicolon. Previously, such passwords caused the DES setup to abort. |

| Reference | DriveLock Enterprise Service (DES)                                                                                                             |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1136   | Fixed an issue that occurred when starting the DriveLock Enterprise Service when a large number of unprocessed events existed in the database. |
|           | An incorrect log file was written during DES setup.                                                                                            |

| Reference        | File Protection                                                                                                                                                                                                |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1051, EI-1064 | Whenever DriveLock detects a change in the loading order of the file system filters that affects the DriveLock File Encryption driver, this change is now corrected and File Encryption will request a reboot. |

| Reference | DriveLock Management Console                                                                                                                                                                  |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-1139   | Fixed an issue with whitelist rules, where DriveLock did not properly store the comments for the allowed serial numbers in the policy, so they were not displayed after reopening the policy. |

| Reference | Microsoft Defender                                                                                                |
|-----------|-------------------------------------------------------------------------------------------------------------------|
| EI-1114   | It was not possible to configure the settings for Microsoft Defender, they always remained at " Not configured ". |

| Reference | Network Pre-Boot Authentication                                                                                                      |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------|
| EI-1134   | A network PBA login was not possible in the time between 18:12h and 24:00h (UTC). The required timestamp was calculated incorrectly. |

| Reference | Self-Service                                                                               |
|-----------|--------------------------------------------------------------------------------------------|
|           | Non-standard ASCII characters can be used again when specifying a reason for self-service. |

## 4.6 Version 2019.2

### 4.6.1 Bug fixes 2019.2

This chapter contains information about errors that are fixed with DriveLock version 2019.2. Our External Issue numbers (EI) serve as references, where applicable.

| Reference | Agent remote control                                                                                                                                                                     |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-613    | Agent remote control will only use secure ports for the connection.                                                                                                                      |
| EI-729    | If SSL is enforced (or even disabled) when a policy is updated, the agent automatically disables port 6064 once the policy is updated.                                                   |
| EI-517    | Use the new <b>Connect As</b> menu item in the DriveLock Agent context menu to set the port and usage of HTTPS. The port can also be specified in the DriveLock Control Center settings. |

| Reference | Application Control                                                         |
|-----------|-----------------------------------------------------------------------------|
| EI-731    | Local whitelist tray icon is displayed in Remote Desktop Session (RDP) now. |

| Reference | BitLocker Management                                                                                                   |
|-----------|------------------------------------------------------------------------------------------------------------------------|
| EI-666    | The error when encrypting a system drive [0x8031002c] was fixed by adjusting the Group Policy registry values.         |
| EI-740    | Existing BitLocker Managed Environments (e.g. MBAM) can be used together with DriveLock now. To do this, the following |

| Reference | BitLocker Management                                                                                                                                                                                                                                                                      |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | DWORD value must be added in the registry key: <code>HKEY_LOCAL_MACHINE \SOFTWARE \CenterTools \DLStatus \RegProtectionLevel</code> (Note: without spaces!). Set the value to 1. Note that you can only change this setting after shutting down the Agent. Restart the system afterwards. |

| Reference | DriveLock Control Center (DCC)                                                                                                        |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------|
| EI-734    | The login screen for the DriveLock Control Center has been extended so that the German text for the user name is no longer truncated. |

| Reference | Device Control                                                                                                |
|-----------|---------------------------------------------------------------------------------------------------------------|
| EI-735    | The registry key "IsAppTermServ" is no longer lost when upgrading the agent.                                  |
| EI-461    | File filter settings (content scanners) are now allowed for portable media devices and are no longer ignored. |

| Reference | Disk Protection                                                     |
|-----------|---------------------------------------------------------------------|
| EI-277    | Switching domains after a WOL no longer results in a domain change. |
| EI-231    | You can now set the entry for encryption certificates to <b>Not</b> |

| Reference | Disk Protection                                                                         |
|-----------|-----------------------------------------------------------------------------------------|
|           | <b>configured</b> in the policy.                                                        |
| EI-579    | You can now delete disk protection certificates from the file repository in the policy. |

| Reference | Encryption-2-Go                                      |
|-----------|------------------------------------------------------|
| EI-137    | You can now set the size limit for encrypted drives. |

| Reference | File Protection                                                                                                                                                                               |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-646    | CSV files can be encrypted now                                                                                                                                                                |
| EI-640    | The <b>User name and password</b> radio button is active now and selected by default.                                                                                                         |
| EI-737    | DLFidEnc no longer crashes during file copy.                                                                                                                                                  |
| EI-426    | When encrypting an external hard drive with DriveLock FFE and performing a defragmentation with Windows, all files are now correctly encrypted and the NTFS file system is no longer damaged. |
| EI-112    | File protection users with read permissions can mount encrypted folders now.                                                                                                                  |
| EI-626    | When File Protection is licensed and Encryption-2-Go is not                                                                                                                                   |

| Reference | File Protection                                                                                                 |
|-----------|-----------------------------------------------------------------------------------------------------------------|
|           | required, you no longer get a warning or error message when configuring the whitelist rules for the drive.      |
| EI-653    | A user with DriveLock certificate will no longer receive an error when attempting to mount an encrypted folder. |

| Reference | Groups and Permissions                                                                                                                          |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-570    | Central File Protection group permissions no longer overwrite individual user permissions if an individual user is included in the added group. |
| EI-633    | You can now remove AD groups from static DriveLock groups.                                                                                      |

| Reference | Management Console (DMC)                                                                                                                            |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-96     | The correct security protocol is now displayed in the GUI for the transfer between server and agent.                                                |
| EI-738    | A LocalHashes.dhb with 0 bytes is no longer created on the client side within the DMC (agent remote control), which led to an event error 222.      |
| EI-321    | The warning "No DriveLock Enterprise Service is available because no valid server connection is configured." no longer pops up while using the DMC. |
| EI-726    | The device scanner now lists all scanned computers.                                                                                                 |

| Reference | Policies                                                                                                                                                                          |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-660    | The Event Log was 'flooded' with events with Event ID 362 after selecting the automatic DriveLock Agent update. We fixed this bug and improved the processing of events.          |
|           | The option <b>Push centrally stored policies to Agents when publishing</b> in the server settings now works without any errors.                                                   |
| EI-617    | When assigning a large number of policies and checking the status using the <code>-showstatus</code> command line command, the display text was truncated. This bug is fixed now. |
| EI-676    | If a policy is based on computer group mapping, the AD group name is now displayed in the agent user interface rather than the AD identifier.                                     |

| Reference | Self-Service                                                                                       |
|-----------|----------------------------------------------------------------------------------------------------|
| EI-718    | It is no longer possible to enter a time in the past in the Self-Service wizard.                   |
| EI-717    | When exporting a Self-Service group to a CSV file, the umlauts (like äöü) are now saved correctly. |

| Reference | Security Awareness                                                                    |
|-----------|---------------------------------------------------------------------------------------|
|           | Campaigns are now displayed only to users defined in the policy and not to all users. |

| Reference | System Management                                                                                                               |
|-----------|---------------------------------------------------------------------------------------------------------------------------------|
| EI-516    | You can no longer enter the same port for agent remote control and HTTPS in the Remote control settings and permissions dialog. |

## 4.6.2 Bug fixes 2019.2 HF1

This chapter contains information about errors that are fixed with DriveLock version 2019.2 HF1.

Our External Issue numbers (EI) serve as reference, where applicable.

| Reference | BitLocker Management                                                                                                                                                                                           |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | Due to a registry key that was blocked by the agent, local group policies were no longer updated properly. As a result, individual group policies were deleted and some applications may have stopped working. |

| Reference | Device Control                                                                                                                                                         |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|           | Drive and device collection functionality was not available because the devices or drives on the collections were not correctly detected when evaluating the policies. |
| EI-820    | The Volume ID functionality for Device Control did not work correctly.                                                                                                 |

| Reference | DriveLock Agent                                                                                                                    |
|-----------|------------------------------------------------------------------------------------------------------------------------------------|
| EI-812    | It is possible to reconnect to the "System Event Notification Service" on Windows 7. The Explorer error message no longer appears. |

| Reference      | DriveLock Control Center                                           |
|----------------|--------------------------------------------------------------------|
| EI-765, EI-749 | The Use FQDN for agent connection setting is available in the DCC. |

| Reference | Events                                                                     |
|-----------|----------------------------------------------------------------------------|
|           | You can create event filter definitions for events without parameters now. |

| Reference | File Protection                                                                                                                                         |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| EI-825    | Paths or file names exceeding 384 characters will raise a blue screen (BSOD) in the File Encryption driver. This bug will be fixed in the next release. |

| Reference | Policies                                                                                                                        |
|-----------|---------------------------------------------------------------------------------------------------------------------------------|
| EI-752    | The DriveLock configuration files were loaded correctly, but the corresponding path was ignored when evaluating their policies. |

### 4.6.3 Bug fixes 2019.2 SP1

#### Important bug fixes in this version

This chapter contains information about errors that are fixed with DriveLock version 2019.2 SP1.

Our External Issue numbers (EI) serve as reference, where applicable.

| Reference | Agent remote control                                                                             |
|-----------|--------------------------------------------------------------------------------------------------|
| EI-749    | Now you can establish a remote agent connection via the DCC independently of the applied filter. |

| Reference | Device Control                                                                                      |
|-----------|-----------------------------------------------------------------------------------------------------|
|           | The popup that was incorrectly displayed no longer appears when a new document is saved.            |
| EI-776    | The error that occurred when loading smartphones after installing DriveLock is fixed.               |
| EI-489    | The issue with Terminal Servers, which sometimes blocked unconfigured network drives, is now fixed. |

| Reference | Disk Protection                                                           |
|-----------|---------------------------------------------------------------------------|
| EI-756    | Hardware compatibility issues related to Disk Protection have been fixed. |

| Reference | DriveLock Agent                                             |
|-----------|-------------------------------------------------------------|
|           | Now, the request code is verified as soon as it is entered. |

| Reference | DriveLock Control Center (DCC)                                         |
|-----------|------------------------------------------------------------------------|
| EI-760    | Reporting/Forensics: The DCC displays the ADSPATH value correctly now. |

| Reference | Encryption-2-Go                                                           |
|-----------|---------------------------------------------------------------------------|
| EI-639    | DriveLock Mobile for MAC OS no longer encrypts the DriveLock-.app folder. |
| EI-643    | When using an encrypted USB device, the CPU is now no longer overloaded.  |

| Reference              | File Protection                                                               |
|------------------------|-------------------------------------------------------------------------------|
| EI-825; EI-884; EI-876 | Several bugs that caused the File Protection driver to crash are fixed.       |
| EI-868                 | You can rename network drives now when File Protection is active.             |
| EI-537                 | Now only administrators can completely decrypt centrally managed directories. |

| Reference | File Protection                                                                                                                    |
|-----------|------------------------------------------------------------------------------------------------------------------------------------|
| EI-628    | When FP is the method used for USB encryption, the automatic decryption dialog now appears every time when connecting a USB drive. |

| Reference | Groups and Permissions                                                                     |
|-----------|--------------------------------------------------------------------------------------------|
| EI-791    | To evaluate the group membership, the Global Catalog server is now also queried correctly. |

| Reference | Management Console (DMC)                                             |
|-----------|----------------------------------------------------------------------|
|           | The MMC is now capable of importing very large CSV files (> 100 kB). |

| Reference | Licensing                                                             |
|-----------|-----------------------------------------------------------------------|
|           | When you update a license, it is no longer assigned to all computers. |

| Reference | Self-Service                                                          |
|-----------|-----------------------------------------------------------------------|
| EI-844    | The Self-service wizard no longer accepts entering times in the past. |

| Reference | Self-Service                                                                                                                    |
|-----------|---------------------------------------------------------------------------------------------------------------------------------|
| EI-538    | Self-service is stopped (after you select the respective checkbox) when the user is connected via RDP with the client computer. |

| Reference | Thin Clients                                                    |
|-----------|-----------------------------------------------------------------|
| EI-794    | The Explorer no longer crashes when used with Terminal Servers. |

## 4.6.4 Bug fixes 2019.2 HF3

### Important bug fixes in this version

This chapter contains information about errors that are fixed with DriveLock version 2019.2 HF3.

Our External Issue numbers (EI) serve as reference, where applicable.

| Reference | Device Control                                                                                                                   |
|-----------|----------------------------------------------------------------------------------------------------------------------------------|
| EI-540    | Improved detection of burning devices and setting correct access rights on volume.                                               |
| EI-1028   | Network drive is not locked any longer with the applied whitelist rule: 00000000-C0D0-C0D0-0001-00000000000A on Terminal Servers |
| EI-1070   | In some configurations, a script was able to access a drive within milliseconds after it was mounted. This bug is fixed now.     |

| Reference | DriveLock Control Center (DCC)                                   |
|-----------|------------------------------------------------------------------|
| EI-1055   | OU filters configured for users now also work for event reports. |

| Reference | File Protection                                                                                                                      |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------|
| EI-1053   | The "[DriveLock File Protection]" menu item could not be disabled via the DriveLock Agent's system tray icon. This bug is fixed now. |

| Reference | DriveLock Pre-Boot Authentication                                                                                                     |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------|
|           | Fixed an issue where the user was prompted to enter a BitLocker recovery key in certain situations after logging in to DriveLock PBA. |

## 5 Known Issues

This chapter contains known issues for this version of DriveLock. Please review this information carefully to reduce testing and support overhead.

### 5.1 DriveLock Management Console

In some cases, the Console crashed when you added a second user after having added a user beforehand. This issue is caused by the Microsoft dialog (AD Picker).

According to our information, this issue is known in Windows 10; please find details [here](#).

As soon as Microsoft has fixed the issue, we will reopen it on our side.

#### Version differences between DMC and DES:

The DMC crashes if the DES in version 2022.1 is used with a lower DMC version.

### 5.2 Known limitations on the agent

#### Updating/installing/uninstalling the agent on Windows 7 x64

The Explorer (explorer.exe) crashes after updating, installing or uninstalling the DriveLock Agent on Windows 7 x64. This only happens in specific scenarios where the Windows command prompt is opened with admin privileges and the system has not been rebooted since the agent was updated/ installed/uninstalled.

### 5.3 DriveLock Enterprise Service (DES)

DES setup may fail when using certificates created with OpenSSL.

### 5.4 Installing Management Components with Group Policies

Note that you cannot install the DriveLock Management Console, the DriveLock Control Center or the DriveLock Enterprise Service using Microsoft Group Policies. Instead, use the DriveLock Installer to install these components as described in the Installation Guide.

### 5.5 Self Service Unlock

If you use the Self Service wizard to unlock connected iPhone devices, it will still be possible to copy pictures manually from the connected iPhone after the unlock period ended.

### 5.6 DriveLock, iOS and iTunes

DriveLock recognizes and controls current generation Apple devices (iPod Touch, iPhone, iPad etc.). For older Apple devices that are only recognized as USB drives no granular control of data transfers is available (for example, iPod Nano).

DriveLock and iTunes use similar multicast DNS responders for automatic device discovery in networks. When installing both DriveLock and iTunes the installation order is important:

- If DriveLock has not been installed yet you can install iTunes at any time. DriveLock can be installed at any later time without any special considerations.
- If DriveLock is already installed on a computer and you later install iTunes you have to run the following command on the computer before you start the iTunes installation: `drivelock -stopdnssd`. Without this step the iTunes installation will fail.

After an update of the iOS operating system on a device, iTunes will automatically start a full synchronization between the computer and the device. This synchronization will fail if DriveLock is configured to block any of the data being synchronized (photos, music, etc.).

## 5.7 DriveLock Device Control

### Universal Camera Devices

In Windows 10, there's a new device class: Universal Cameras; it is used for connected or integrated web cameras that do not have specific device drivers.

Currently, you cannot manage this device class with DriveLock.



Note: To control these devices, please install the vendor's driver that comes with the product. Then DriveLock automatically recognizes the correct device class.

### Windows Portable Devices (WPD)

Locking "Windows Portable devices" prevented that some Windows Mobile Devices could be synchronized via "Windows Mobile Device Center", although the special device was included in a whitelist.

Windows starting from Windows Vista and later uses a new "User-mode Driver Framework" for this kind of devices. DriveLock now includes this type of driver.

The driver is deactivated on the following systems because of a malfunction in the Microsoft operating system:

- Windows 8
- Windows 8.1 without Hotfix KB3082808
- Windows 10 older than version 1607

## CD-ROM drives

DriveLock only shows a usage policy once when a CD is inserted. When ejecting the CD and inserting a new one, the usage policy does not appear any more but the new CD is blocked nonetheless. When you restart DriveLock, the usage policy appears again.



Note: This is because DriveLock only recognizes the actual device in the policy (CD-ROM drive), not the content (CD-ROM).

## Files blocked for a short time

Files may be blocked on a USB flash drive for short time during a configuration update when a file filter is configured and access is permitted for specific users or groups.

## Windows Portable Devices on Citrix Generic Channel

The Windows Portable Device API does not return VID, PID and S/N in this configuration. Since the driver can retrieve the correct information, there are two workarounds for this problem:

- Connect the device to any agent and create a whitelist rule. The driver is able to obtain VID, PID and S/N, therefore the locking will be working as expected.
- Create a device collection and insert the device based on the Hardware ID. This is possible even for devices connected to the Citrix Generic Channel. Then create a whitelist rule for the collection (Reference: EI-1705)

## 5.8 DriveLock Disk Protection

### Windows Inplace Upgrade

If you have enabled a certain number of automatic logins for the PBA (dlfdecmd ENABLEAUTOLOGON <n>) before updating to a current Windows 10 version, the automatic logon is active throughout the upgrade process. However, since the <n> counter cannot be updated during the process, we recommend that you just set it to 1 so that after upgrading, after another reboot, there is only one automatic login followed by another user login to the PBA.

### Antivirus software

Antivirus protection software may cause the DriveLock Disk Protection installation to fail if the antivirus software quarantines files in the hidden `C:\SECURDSK` folder. If this occurs, please disable your antivirus protection for the duration of the Disk Protection installation. We recommend that you configure your virus scanner with an exception for the folder.

## Application Control

We strongly recommend that you disable Application Control as long as it is active in whitelisted mode for the duration of the Disk Protection installation to prevent programs required for the installation from being blocked.

## Hibernation

Hibernation will not work while a disk is encrypted or decrypted. After complete encryption or decryption windows has to be restarted once to make hibernate work again.

## UEFI mode



Note: Not all hardware vendors implement the complete UEFI functionality. You should not use the UEFI mode with UEFI versions lower than 2.3.1.

- The PBA provided by version 2019.2 is only available for Windows 10 systems, because the driver signatures from Microsoft required for the hard disk encryption components are only valid for this operating system.
- The PBA for UEFI mode may cause issues with PS/2 input devices (e.g. built-in keyboards).
- With VMWare Workstation 15 and also with a few hardware manufacturers, our test results revealed conflicts with mouse and keyboard drivers of the UEFI firmware, so that keyboard input in the PBA is not possible. In this case, you can use the "k" key to prevent the DriveLock PBA drivers from loading once when you start the computer. After Windows logon to the client, you can then run the `dlsetpb /disablekbddrivers` command in an administrator command line to permanently disable the DriveLock PBA keyboard drivers. Be aware that the standard keyboard layout of the firmware is loaded in the PBA login mask, which usually is an EN-US layout, so special characters may differ.

Introducing the combined driver as of version 2020.1 solves the issue on some systems (including VM Ware Workstation 15).

For more information on hotkeys and function keys, see the corresponding chapter in the BitLocker Management documentation at [DriveLock Online Help](#).

Note the following information:

- DriveLock 7.6.6 and higher supports UEFI Secure Boot.
- If you update the firmware, the NVRAM variables on the mainboard that DriveLock requires may be deleted. We strongly recommend that you install the firmware

updates for the mainboard /UEFI before installing DriveLock PBA / FDE ( this also applies to recently purchased devices or to bug fixes).

- A 32 bit Windows operating system or 32 bit DriveLock cannot be installed on 64 bit capable hardware. Please use a 64 bit version of a Windows operating system and DriveLock instead.
- There is still a limitation to disks up to a maximum of 2 TB disk size.
- Some HP computers always have Windows in position 1 of the UEFI boot order and the DriveLock PBA has to be selected manually in the UEFI boot menu. In this case fast boot has to be switched off in UEFI to keep the DriveLock PBA at position one.

### BIOS mode

On a small number of computer models the default DriveLock Disk Protection pre-boot environment configuration may not work correctly and cause the computer to become unresponsive. If this occurs turn off the computer and restart it while pressing the `SHIFT-Taste` key. When prompted select the option to use the 16-bit pre-boot operating environment.

Due to an issue in Windows 10 Version 1709 and newer, DriveLock Disk Protection for BIOS cannot identify the correct disk if more than one hard disk is connected to the system. Therefore Disk Protection for BIOS is not yet released for Windows 10 1709 systems with more than one hard disk attached until Microsoft provides a fix for this issue.



Note: An additional technical whitepaper with information on updating to a newer Windows version with DriveLock Disk Protection installed is available for customers in our Support Portal.

### Workaround for Windows Update from 1709 to 1903 while encrypting drive C: with Disk Protection:

Reference: EI-686)

1. Decrypt drive C:
2. Update Windows 10 from 1709 to 1903
3. Encrypt drive C:

### Requirements for Disk Protection:

Disk Protection is not supported for Windows 7 on UEFI systems.

**Restart after installation of PBA on Toshiba PORTEGE Z930:**

Reference: EI-751)

After activating Disk Protection with PBA and restarting the above-mentioned notebooks, Windows cannot be started and so the notebook cannot be encrypted. Our team is working on a solution.

**Workaround for DriveLock update from 7.7.x with Disk Protection with PBA enabled to version 2019.2 or newer**

First, update from 7.7.x to version 7.9.x. Only then do you update to version 2019.2. Please contact our support for further questions.

**5.9 DriveLock File Protection****Microsoft OneDrive**

- With Microsoft OneDrive, Microsoft Office may synchronize directly with OneDrive instead of writing the file to the local folder first. Then the DriveLock encryption driver is not involved and the Office files will not be encrypted in the Cloud. To stop this behavior, deselect **Use Office 2016 to sync files I open** or similar settings in OneDrive. Make sure that Office files as other files always are stored locally.

**NetApp**

- Currently, some incompatibility persists between DriveLock's encryption driver and certain NetApp SAN drivers or systems that cannot yet be more precisely defined. Please check the functionality you require before using File Protection in this system environment. We are happy to help you here to analyze the issue in detail if necessary.

**Windows 10 clients with Kaspersky Endpoint Security 10.3.0.6294**

- The blue screen error persists after activating DriveLock File Protection (DLFIdEnc.sys).

**Accessing encrypted folders**

- Access to encrypted folders on drives that are not mounted with drive letters but as volume mountpoints is not supported.

**Cancel folder encryption**

- We do not recommend canceling the encryption/decryption of folders. If this happens (has happened) nevertheless, do not delete the database file, as the status of the running files will be lost.

## File Protection and USB drives

- You cannot use DriveLock File Protection to fully encrypt a connected USB drive if the drive already contains an encrypted folder. In this case the following message appears "Cannot read management information from the encrypted folder".

## Distributed File System (DFS)

- DriveLock File Protection basically also supports storing encrypted directories on a network drive with Distributed File System (DFS). DriveLock File Protection basically also supports storing encrypted directories on a network drive with Distributed File System (DFS). Since DFS and the associated storage system can contain customer-specific characteristics, however, we recommend that you test encrypted directories in detail before using them. . Access to the folder mapped as a drive is denied if the DFS reference member is not selected for the mapping.

## 5.10 DriveLock Pre-Boot Authentication

- Hardware must support the TCP4 UEFI protocol for the DriveLock PBA network functionality to work. For this reason, some systems may run into trouble if the UEFI BIOS does not support the required network connections. This is specifically the case with the following systems:
  - Fujitsu LifeBook E459. (Reference: EI-1303)
  - Fujitsu LifeBook U772
  - Acer Spin SP11-33
  - Acer Spin SP513-53N
  - Dell Inspiron 7347
- On some DELL devices, the implementation of time counting differs from the standard and may result in a longer time span than expected. Unfortunately, we cannot solve this hardware-related issue through programming. (Reference: EI-1668)
- DriveLock uses its own UEFI driver for keyboards by default (either a simple one or a combination driver with mouse support) to offer international keyboard layouts within the PBA as well. It is loaded with the help of a UEFI standard interface. On some models, this interface specified in the UEFI standard is not implemented correctly or not at all. In such cases, it is possible to disable loading the DriveLock driver, either using the command line command "dlsetpb /KD-" or via a setting within the policy available in DriveLock version 2021.2.  
Note that the default driver implemented by the manufacturer is used here, which usually only supports an English keyboard layout.

- If you add additional unencrypted disks to an already encrypted system, always make sure to access the new disks after the existing disks to avoid any access issues to the EFS or failure to synchronize users. (Reference: EI-1762)
- When the PBA is installed, the Windows logon screen provides logon for other users, but does not show the user who was logged on last time. This occurs because of the "Fast User Switching" feature used for that purpose in Windows and its implementation by Microsoft. (Referenz: EI-1731)
- Warning: In the event of a time change (for example, winter time to daylight saving time), you run into a mismatch between server and system time if your DriveLock Agents were shut down prior to the change (thus using the 'old' time), but the time on your server has already been changed. In this case, the login to the network PBA is blocked. End users must select a different logon method once (user name / password entry) or you need to adjust the system time manually. Once both times are synchronized, logging into the network PBA will work again. (Reference EI-1817)
- The DriveLock PBA requires smart card readers to have a CCID V1.1 compliant interface.

## 5.11 Encryption

### Setting the encryption method for forced encryption of an external storage device

If the administrator did not specify the encryption method, a dialog for selecting the encryption method (Encryption-2-Go, Disk Protection, BitLocker To Go) appears on the DriveLock agent when connecting the external storage device. In some cases, however, this dialog appears incorrectly even for SD card readers without media. Our team is working on a solution.

## 5.12 DriveLock Mobile Encryption

### DriveLock Mobile Encryption: NTFS/EXFAT

DriveLock Mobile Encryption (Encryption 2-Go) can mount NTFS/EXFAT containers as read-only.

### Default enforced encryption settings

If you select the option "Fill any remaining empty space on drives", a small amount of storage space (very few MB) may remain free for technical reasons when calculating the available space. (Reference: EI-1784)

## 5.13 BitLocker Management

### Supported versions and editions:

DriveLock BitLocker Management supports the following operating systems:

- Windows 7 SP1 Enterprise and Ultimate, 64 bit, TPM chip required
- Windows 8.1 Pro and Enterprise, 32/64 bit
- Windows 10 Pro and Enterprise, 32/64 bit

### Native BitLocker environment

 Note: Starting with version 2019.1, you don't have to use the native BitLocker administration or group policies to decrypt computers that were previously encrypted with native BitLocker; these system environments can be managed directly now. DriveLock detects native BitLocker encryption automatically and creates new recovery information. The drives are only decrypted and encrypted automatically if the encryption algorithm configured in the DriveLock policy differs from the current algorithm.

After that, you can use DriveLock BitLocker Management to manage your computers and securely store and utilize the recovery information.

### Using passwords

With DriveLock BitLocker Management, the misleading distinction between PINs, passphrases and passwords is simplified by simply using the term "password". Also, this password is automatically used in the correct BitLocker format, either as a PIN or as a passphrase.

Since Microsoft has different requirements for the complexity of PIN and passphrase, the following restrictions apply to the password:

- Minimum: 8 characters In some cases 6 characters (numbers) are also accepted. For more information see the current BitLocker Management documentation on [DriveLock Online Help](#).
- Maximum: 20 characters

 Warning: Note that BitLocker's own PBA only provides English keyboard layouts, which means that using special characters as part of the password may cause login issues.

## Encrypting extended disks

Microsoft BitLocker limitations prevent external hard disks (data disks) from being encrypted if you have selected the "TPM only (no password)" mode, since BitLocker expects you to enter a password (BitLocker terminology: passphrase) for these extended drives.

## Group policy configuration

For technical reasons, you cannot configure computer-specific passwords via DriveLock Control Center if you have distributed the DriveLock BitLocker configuration to the agents via Group Policy.

In this case, the DriveLock Agent ignores the required machine-specific policies.

## Encryption on Windows 7 agents

On Windows 7 agents, the following error may occur when you use the new execution options added in DriveLock 2020.2: BitLocker does not encrypt on Windows 7 if the "when the screen saver is configured and active" and "when no application is running in full screen mode" options are enabled.

## Moving from Disk Protection to BitLocker Management

You must remove Disk Protection with the appropriate policy setting before you can use BitLocker Management.

## Encryption with BitLocker To Go

A USB flash drive was not mounted after encrypting it with an administrative password. To solve the issue, remove the USB flash drive first and then plug it back in.

## 5.14 DriveLock Operations Center (DOC)

### Old versions of DOC.exe are no longer supported

You will need to manually uninstall old DOC.exe versions starting with version 2021.2. Note that these old versions will no longer work with an updated DES and are therefore discontinued.

### Version conflict when calling the RSoP

If a DriveLock agent has version 2021.2 installed, at least version 2021.2 is also required for the DriveLock Management Console (DMC) to display RSoP correctly.

### Multiple selection of computers in the Computers view

If you select several computers in the Computers view and then select the **Run actions on computer** command in the upper right menu to enable the trace for these computers,

tracing is only started for the first selected computer. The others neither start the tracing nor report an error. Our team is working on a solution.

### **Login to the DOC for users who have been removed from an AD group**

Users can still log in to the DOC even if they have already been removed from an AD group and therefore no longer have authorization for logging in. This is because group memberships for a user are read from the group token. This information is only updated at certain intervals. Our team is working on a solution.

### **Export lists to Excel**

It depends on the available resources how many lists you can export. We recommend that you set the filters so that no more than 20,000 entries are exported. A higher number of entries may cause the action to be aborted or the exported list to remain empty. (EI-1379)

### **DOC Companion**

The drive collection does not show drives when the policy is opened with DOC Companion.

## **5.15 DriveLock Security Awareness**

### **Changed content for the Security Awareness Content AddOn**

Starting with version 2019.1, DriveLock no longer supports Dutch campaign contents. Instead, we support French now.

 Warning: Note that the Dutch content will be automatically deleted from the DES when you update to a version higher than 2019.1.

## **5.16 DriveLock and Thin Clients**

Please note the following restrictions when using DriveLock and Thin Clients:

- Security Awareness version 2019.2 cannot be used on IGEL clients. We are working on a solution and will provide it with one of our next releases.
- The “Fill any remaining space on drives” option does not work correctly when used for encrypting a DriveLock container via a Thin Client.

## 6 End Of Life Announcement

DriveLock sends out a newsletter in time to inform you about the end of support and maintenance for a specific DriveLock version.

 Note: We recommend that all our customers install the latest DriveLock version.

**For the following versions, the corresponding End-Of-Life (EoL) data apply:**

| Version        | Continued Customer Care Support |
|----------------|---------------------------------|
| 7.9 and 2019.1 | EoL - not supported any more    |
| 2019.2         | May 2022                        |
| 2020.1         | December 2021                   |
| 2020.2         | May 2023                        |
| 2021.1         | November 2022                   |
| 2021.2         | May 2024                        |
| 2022.1         | September 2023                  |

### Support cycles:

Support periods for new product versions are adjusted to match the support period for Windows 10 Enterprise Edition, released during the same period of the year (release spring: approx. 18 months, release fall: approx. 30 months). When a new version is released, we also publish the support end of this version.

Maintenance updates and code fixes for bugs and critical issues will be released during this period. We also respond to inquiries via phone, email and Self-Service, provided by DriveLock's Product Support Team and related technical assistance websites.

**Upgrades:**

Customers who have previous product versions and a valid maintenance contract can upgrade the environment to the latest product version.

**End of life of features:**

We have stopped developing the DCC and it will no longer be part of our product. DriveLock 2021.2 is the last version that officially supports the DCC until May 2024.

## 7 DriveLock Test Installation

If you want to have a detailed look at DriveLock and test the product, you can request a trial through the DriveLock website. Just follow the links on our website <https://www.drivelock.de/>.

We will provide you with a cloud-based tenant. This way, you can fully focus on the DriveLock Agent and DriveLock's protection functionality.

Once you have registered for a test, we will send you several emails with information to support your testing. See <https://www.drivelock.de/cloud-testversion-information> for a summary.

Please contact [info@drivelock.com](mailto:info@drivelock.com) / [sales@drivelock.com](mailto:sales@drivelock.com) for more information and assistance with your testing.

## Copyright

Information in this document, including URL and other Internet Web site references, is subject to change without notice. Unless otherwise noted, the example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted herein are fictitious, and no association with any real company, organization, product, domain name, e-mail address, logo, person, place, or event is intended or should be inferred. Complying with all applicable copyright laws is the responsibility of the user.

© 2022 DriveLock SE. All rights reserved.

DriveLock and others are either registered trademarks or trademarks of or its subsidiaries in the United States and/or other countries.

The names of actual companies and products mentioned herein may be the trademarks of their respective owners.